A Computing Framework for Integrating Interactive Visualization in HPCC Applications

Gang Cheng, Geoffrey C. Fox, Tseng-Hui Lin and Tomasz Haupt

Northeast Parallel Architectures Center, Syracuse University, Syracuse, NY 13244

Abstract

Network-based concurrent computing and interactive data visualization are two important components in industry applications of high performance computing and communication. We propose an execution framework to build interactive remote visualization systems for real world applications on heterogeneous parallel and distributed computers. Using a dataflow model of a commercial visualization software AVS in three case studies. we demonstrate a simple, effective and modular approach to couple parallel simulation modules into an interactive remote visualization environment. The applications described in this paper are drawn from our industry projects in financial modeling, computational electromagnetics and computational chemistry.

1 Introduction

Scientific visualization has traditionally been carried out interactively on workstations, or in post-processing or batch on super computers. With advances in high performance computing systems and networking technologies, interactive visualization in a distributed environment becomes feasible. In a remote visualization environment, data, I/O, computation and user interaction are physically distributed through high-speed networking to achieve high performance and optimal use of various resources required by the application task. Seamless integration of high performance computing systems with graphics workstations and traditional scientific visualization is not only feasible, but will be a common practice with real-time application systems.

Advances in parallel computing systems and network technology provide new opportunities for implementing computationally intensive applications. Applications that integrate modeling and simulation with large scale information processing often require an interactive graphical user interface (GUI) in a real-time computing environment. Most GUIs are event-driven, and serial in nature, making them unsuitable for parallel implementation. On the other hand, visualization tools for parallel systems often require special hardware support, or are developed for a specific hardware/software system and are not portable. Parallel computing environment of the future will likely be based on a heterogeneous networked computing system, and be required to solve applications with various requirements in scientific computation, communication, programming models, memory hierarchies, I/O, database management and visualization. Network-based concurrent computing and advanced data visualization are two important components in real-world applications of high per-

formance computing and communication(HPCC), especially for industrial problems requiring real-time simulation/modeling, information processing and system integration.

During the past two years, Northeast Parallel Architectures Center (NPAC) at Syracuse University has actively engaged in several research and application projects that require interactive data visualization and distributed and parallel processing. We have developed real-time parallel numerical simulation/modeling applications in the areas of financial modeling[16, 19], computational electromagnetics[17], computational chemistry[13] and environmental modeling[18]. These applications use a range of parallel and distributed systems, from MPP machines including CM2/CM5, DECmpp-12000, IBM SP2 to networked heterogeneous workstation clusters such as DEC Alpha Farm and coupled MPPs and workstations. These projects are part of an major HPCC technology transfer program InfoMall[3] developed at NPAC which consists of a set of interactive distributed high performance information systems, collectively called InfoVision [2] (INFOrmation, Video, Imagery, and SImulation ON-demand). Targeted at the state-of-the-art applications and enabling technology on NYNET, a regional ATM-based wide area network, and the utilization of supercomputing resource at NPAC, InfoVision focuses on real-time information production, analysis, access and integration on distributed and parallel computing systems – allow geographically located regional end-user to interactively access multimedia information and to remotely perform parallel simulations on supercomputers over the high-speed NYNET.

As a core enabling technology in simulation on-demand applications, interactive software integration environment plays a central role in coupling parallel and distributed computing, interactive remote user-interface, advanced data visualization and transparent networking to support real-time simulations over a heterogeneous computing and networking environment.

In this paper, we describe our experience in building interactive visualization systems for the InfoVision simulation-on-demand projects. We use Application Visualization System (AVS) as an integration framework to facilitate both networking and scientific data visualization in all the three case studies. This paper is organized as follows: in Section 2, we briefly review some related work in embedding parallel applications within the framework of modular distributed visualization systems. In Section 3, we introduce AVS and propose a distributed visualization and computing framework that is built on AVS's dataflow model and to be elaborated in later sections when applied to specific applications and parallel systems. Section 4 describes a prototype visualization system for a financial option price modeling application originally implemented on a CM5 and a DECmpp-12000 and ported to an IBM SP2 and a DEC Alpha Farm; A remote visualization environment using the AVS model for an electromagnetic scattering simulation on a CM5 and networked workstations is given in Section 5 to demonstrate the effectiveness of this framework. In Section 6, we describe our experience in porting a software package MOPAC to parallel systems and creating a data visualization for computational chemistry applications. Finally we conclude in Section 7.

2 Related Work

Research and applications in distributed visualization environments have been very active in HPCC community since the early 1980's. Interactive visualization is identified as a critical component in the national HPCC initiatives[21, 22]. There are many efforts in developing interactive distributed visualization applications on parallel systems in the framework of AVS dataflow model [26, 27, 28, 29, 30]. Most of them, however, focused on customized solutions such that the front-end visualization/graphics components are tightly coupled with back-end parallel engines in which specialized graphics hardware is usually required to support high-end graphics capability. Our approach is focused on a loosely coupled visualization and computing framework portable to different distributed computing system configurations, to be able to support a general interactive software development environment for HPCC applications[20].

Among several similar work towards this direction include CM/AVS and MP/Express. CM/AVS [23, 24] developed by Thinking Machines is a modular visualization system in which AVS is used as the front-end visual programming interface for scientific data visualization, and is tightly coupled with the CM-5 parallel supercomputer for back-end parallel computations. The major difference between CM/AVS and distributed AVS environment is that instead of conventional TCP/IP sockets and UNIX shared memory, specialized CM-5 shared memory regions or CM-domain sockets are used in CM/AVS to exchange data among distributed parallel modules on CM-5 processors partitions.

MP/Express [25], a research project in AVS Inc., is an enhanced AVS/Express for building parallel and distributed AVS applications with a visually-based software development tool. It incorporates a middle communication layer between the AVS kernel and application modules such that distributed modules can communicate with each other using the portable message-passing layer and a data layout system for automatic data distribution among multiple node processes of a distributed module in SPMD (Single Program Multiple Data) paradigm. The serialized data transfer channels between parallel modules found in AVS become parallel channels in MP/Express, and automatic data layout for splitting and recombining data sets in AVS data types is available to module developers.

3 A Distributed Visualization and Computing Model in AVS

3.1 Application Visualization System

AVS[6] is a software development toolkit based on a dataflow model for scientific data visualization and process control. It incorporates visualization, graphics, visual programming, process management and networking into a single comprehensive software development environment.

The AVS dataflow is a model of parallel computation in which a flow network of autonomous processes compute by passing object data along arcs interconnected by input/output ports. Each module, represented as an individual UNIX process,

fires autonomously as soon as new input object it requires arrives on its input ports. It then produces output object that flows on its output port thus triggers further computations. A set of base communication objects is pre-defined such as numbers and fields (n-dimensional arrays) and a collection of computational modules is provided that transform sets of input objects into sets of output objects. AVS itself offers an extensive library of ready-to-use modules mostly for graphics programming and filtering, as well as it specifies the protocol for developing and including user modules into the system. Specific applications are assembled from reusable modules with the aid of visual network editing tools. Modules are visualized as nodes, ports as terminals, and communication objects as links of an interactively constructed dataflow network.

Both process control and data transfer among processes in AVS are in a modular fashion and are completely transparent to the programmer. AVS provides a data-channel abstraction that transparently handles module connectivity and ports type-checking. The module programmer needs only to define the input and output ports in AVS predefined data types by using a set of AVS routines and micros. Message passing occurs at a high level of data abstraction and only through the input and output ports. Each AVS application includes an AVS kernel and a set of modules, specified by a dataflow network. The AVS kernel executes network specification and instantiates module processes as well as the lower level inter-modular communication links, based on the RPC/XDR UNIX network protocol. The important feature of the AVS execution model is that it supports remote module execution in which various nodes of the computational graph can be executed on distributed machines on a local or wide area network.

3.2 A Dataflow-based Distributed Visualization and Computing Model

In a typical remote visualization environment, a simulation cycle is started from a GUI module running on a local machine, with simulation parameters are represented as slide buttons or dials, providing real-time instrumentation of the simulation's progress as well as simulation steering (changing simulation parameters before a new simulation cycle). The computational task of the simulation is usually decomposed into several computationally independent sub-tasks which are represented as computing modules distributed to different remote machines. Input data for the simulation are collected from the GUI for user runtime interaction, from disk files, or both sources, and broadcasted to the computing modules on the remote machines. There is no or little data transfer among modules on different remote machines during the course of major simulation computations. A remote machine may be a workstation or a supercomputer, whichever architecture and computational power best suited to the decomposed sub-task. The simulation ends with some kind of GUI rendering/viewing modules that run on the local machine and use results generated from remote modules. Fundamentally, this is a dataflow (data-driven) programming model, in which activation of a module process is triggered solely by the availability of input data from other module processes or the GUI on the same or different machines.

FIG. 1. *A general visualization/computing model*

This general model is well suited to rapid-prototyping for certain simulation and modeling applications that require real-time visualization and distributed computing. At the software environment level, this model only requires support of high level data visualization and networking facilities. Most importantly, this data flow based model is well supported by most commercially available data visualization packages, such as AVS[1] from AVS Inc., Explorer [7] from Silicon Graphics Inc. and Data Explorer from IBM.

As shown in Figure 1, using the data-flow programming model in AVS, message passing among modules on the same machine and different machines are identical and completely transparent to the module programmer. The AVS kernel supervises data transfer which is eventually carried out by TCP/IP at a lower level. The module programmer needs only to define module input and output ports in AVS predefined data types. Message passing among AVS modules occurs only through I/O ports and uses AVS's IPC or RPC protocol. A set of routines for initializing and describing modules to AVS, as well as parameter handling, accessing data, error handling and coroutine event handling are provided. Data sources and destinations can be flexibly defined by visually connecting module input and output ports using a network editor.

Data transfers between host and node programs of a parallel module rely on either portable message passing protocols in implementing the parallel module such as PVM and MPI, or native protocols specific to the parallel system such as CMMD, CMFortran on a CM5, MPL on a IBM SP2 or HPF on a DECmpp. They are strictly confined within a parallel module. Message passing between two parallel modules on different machines must go through the dataflow channel between the two sequential AVS modules embedded in the host parts of the parallel programs.

3.3 Performance Analysis

A generalized performance model of our networked system is shown in Figure 2.1. In one complete modeling cycle, starting with broadcast of new data from M_I, and ending with renderings on M_h, let t_{calc} be the summed calculation time on all machines and t_{comm} be the summed communication time in the system. Let T_d, T_s be the total time to complete such a cycle in the distributed system and in a single-machine system, respectively. Other symbols are defined as follows: c_{k} – communication time of required message passing from M_I to M_k; d_{k} – communication time of required message passing from M_k to M_h; m_{k} – calculation time of performing required computation on M_k; r_{k} – calculation time of performing required rendering by P_k on M_k; t'_{calc} – the total calculation time on a single-machine system; m'_{k} – calculation time of performing required computation on a single machine system.

In a single-machine system, $M_I = M_h = M_1 = M_2 = \cdots = M_n, t_{\text{comm}} = 0$ and $T_s = t'_{\text{calc}} = \sum_{k=1}^{n} (m'_k + r_k)$. In the distributed system based on TCP/IP protocol, we observe: sequential message passing from M_I to M_k, although the sending order can be scheduled; execution of computing process on M_k upon receiving new message from M_I; and sequential rendering of process P_k on a single-processor machine M_h,

where each P_k is activated only after receiving a new message from M_k, and no other $P_j (j \neq k)$ is running on M_h.

Calculation and communication among different machines in the system are pipelined. We can overlap the following processes: (1) c_k with m_j, d_j, and r_j; (2) m_k with d_j and r_j; and (3) d_k with r_j. Figure 2.2 illustrates this overlap of processes in system of $(n = 2)$ machines. For each machine M_k, the total time to complete a cycle is $T_d = c_k + m_k + d_k + r_k + i_k$, where i_k is the idle time of M_k in the cycle, excluding the waiting time r_k for the rendering on M_h. Thus, $nT_d = t_{\text{comm}} + t_{\text{calc}} + t_{\text{idle}}$, where $t_{\text{comm}} = \sum_{k=1}^{n}(c_k + d_k)$, $t_{\text{calc}} = \sum_{k=1}^{n}(m_k + r_k)$, and $t_{\text{idle}} = \sum_{k=1}^{n} i_k$.

The speed-up S of a distributed system over a single-machine system is:

$$S = \frac{T_s}{T_d} = \frac{n}{\frac{t_{\text{calc}}}{t'_{\text{calc}}} + \frac{t_{\text{comm}}}{t'_{\text{calc}}} + \frac{t_{\text{idle}}}{t'_{\text{calc}}}},$$

Speedup depends on four components: (1) n, the number of distributed computing modules; (2) $t_{\text{calc}}/t'_{\text{calc}}$, the ratio of total calculation time on the distributed system to calculation time on a single-machine system; (3) $t_{\text{comm}}/t'_{calc}$, the ratio of total communication time in the distributed system to calculation time on a single-machine system; and (4) $t_{\text{idle}}/t'_{\text{calc}}$, the ratio of total idle time in the distributed system to calculation time on a single-machine system. As Figure 5 illustrates, for a given application on a given system (fixed c_{k}, d_{k},m_{k},r_{k}) t_{idle} depends on the order of messages sent from M_I to M_k, making this a scheduling problem. In the best case, $t_{\text{idle}} = \sum_{k=1}^{n-1} c_k(n-k) + \sum_{k=1}^{n} a_k r_k$, where $\{a_1, a_2, \ldots, a_n\}$ is a permutation of the set $\{0, 1, \ldots, n-1\}$.

4 A Financial Modeling Application

4.1 Introduction and Problem Description

Financial modeling represents a promising industry application of high performance computing. Stock option pricing models are used to calculate a price for an option contract based on a set of market variables, (e.g. exercise price, risk-free rate, time to maturity) and a set of model parameters. Model price estimates are highly sensitive to parameter values for volatility of stock price, variance of the volatility, and correlation between volatility and stock price. These model parameters are not directly observable, and must be estimated from market data. Using optimization techniques for model parameter estimation holds great promise for improving model accuracy. In previous work, parallel stock option pricing models were developed for a CM-5 and a DECmpp-12000[4, 5], and later ported to an IBM SP2 and a DEC Alpha cluster. These parallel models run approximately two orders of magnitude faster than sequential models on high-end workstations.

We use a set of four option pricing models in this study. Simple models treat stock price volatility as a constant, and price only European (option exercised only at maturity of contract) options. More sophisticated models incorporate stochastic

volatility processes, and price American contracts (option exercised at any time in life of contract)[14, 15]. The models with stochastic volatility are computationally intensive and have significant communication requirements. The four pricing models are: BS - the Black-Scholes constant volatility, European model; AMC - the American binomial, constant volatility model; EUS - the European binomial, stochastic volatility model; and AMS - the American binomial, stochastic volatility model. Detailed descriptions about these four models can be found in [14, 4].

Analytic models are useful tools in the financial market, but require expert interpretation. To further evaluate and optimize pricing models to run in a realistic application environment, we combine high performance computing modules for real-time pricing with real-time visualization of model results and market conditions, and a graphical user interface allowing expert interaction with pricing models. We envision a market expert using such a system to start and stop a set of models, adjust model parameters, and call optimization routines according to dynamically changing market conditions.

4.2 System Configuration and Integration

Using the stock option price modeling application as a case study, we demonstrate a simple, effective and modular approach to coupling network-based concurrent modules into an interactive remote visualization environment as proposed in Section 3. A prototype system on two different system configuration is developed to show the portability of this framework, in which parallel option pricing models are implemented on two meta-computer systems: one with two MPP machines - a 32-node CM5 and a 8K-node DECmpp-12000; the other with two distributed systems - an Ethernet-based IBM SP2 and a cluster of DEC Alpha workstations networked by a FDDI-based GIGA-switch. They are coupled with an interactive graphical user interface over the NYNET ATM-based wide area network. AVS is used to integrate massively parallel processing, workstation based visualization, an interactive system control, and distributed I/O modules.

Configuration 1 - NYNET + CM5 + DECmpp-12000 + Workstations

As shown in Figure 3.1, the computing infrastructure for this application consists of four compute nodes, two file servers, and an AVS server machine, all connected by a local network. The AVS kernel runs on a SUN10 workstation which acts both as an AVS server to coordinate data-flow and top-level concurrent control among remote modules, and as a network gateway which links the NPAC in-house parallel machines to the regional end-user through the NYNET. The ATM-based link is built around two Fore switches that operate at 155 Mbps (OC3c) while the wide area network portion of the network operates at OC48(2400 Mbps) speed.

The four option pricing models run on the four remote compute nodes respectively, each employs an optimized algorithm to the underlying (parallel) machine architecture: BS model on a DEC5000, AMC model on a SUN4, EUS model on a CM-5 and AMS on a DECmpp-12000. The DECmpp-12000 is a massively parallel SIMD

system with 8192 processors. Each RISC-like processor has a control processor, forty 32-bit registers, and 16 KBytes of RAM. All the processor elements are arranged in a rectangular two-dimensional grid and are tightly coupled with a DEC5000 front-end workstation. The theoretical peak performance is 650 Mflops DP. The CM-5 is a parallel MIMD machine with 32 processing nodes. Each processing node consists of a SPARC processor for control, four proprietary vector units for numerical computation, and 32 MBytes of RAM. The control node of the CM-5 is a SUN4 workstation. The theoretical peak performance is 4 Gflops. The two sequential compute nodes are a DEC5000 and a SUN4.

While displayed on the end-user's home machine, a user interface process actually runs on a remote SUN4 server which combines user runtime input (model parameters, network configuration) with historical market databases stored on disk,

and broadcasts this data to remote compute nodes. Top-level system synchronization occurs with each broadcast.

An IBM RS/6000 is used as a file server for non-graphical output of model data. In this application, model prices calculated at remote compute nodes, along with market data, are written to a database on the output file server for later analysis.

The heterogeneous computing system integrates diverse functions - computation, visualization, and system control over a diverse set of hardware. We use a mix of programming languages on the remote compute nodes - Fortran77 on the DEC5000, C on the SUN4, CMFortran on the CM-5, and MPL (data parallel C) on the DECmpp-12000. At the operating system level, all remote modules are compiled and linked as stand-alone programs. Input and output ports are defined in modules by the programmer using specific library routines provided by AVS. Each module represents a process.

There are two source of input data: historical market data read from disk files, and runtime input of model parameters by the user through a GUI on the home machine. Output from all four models is rendered in a graphics window of the GUI and displayed numerically in a shell window, both on the home machine, and written to a database on the file server.

Figure 4 shows the GUI for managing user runtime input and output, and the system configuration. Runtime input includes user defined model parameters and system execution modes (continues, step or pause). Outputs include 2-dimensional displays of model and market prices calculated by the compute nodes. The system configuration includes choice of pricing models, network configurations and interface layouts.

Configuration 2 - NYNET + IBM SP2 + DEC Alpha Farm + Workstations

Figure 3.2 is the second system configuration using the same visualization/computing framework while the two parallel pricing models are now ported to two clusters instead of the two MPPs in the previous configuration.

The two parallel pricing models (EUS model and AMS model) are implemented in PVM and run respectively on a 8-node IBM SP2, networked by an Ethernet at the time of evaluation, and a 8-node DEC Alpha cluster inter-connected by a FDDI-based GIGA-switch. They are coupled under the proposed AVS environment with the other two sequential simple models (BS model and AMC model) running on a SUN4 and a DEC5000 workstation, respectively. The nodal processor of SP2 is IBM RISC/6000 processor running at 62.5 MHz. The DEC Alpha farm consists of 8 Alpha model 4000 workstations which are supported by a high performance networking backbone of a dedicated, switched FDDI segments. The GIGA-switch provides full FDDI bandwidth and low latency switching to every workstation in the farm.

4.3 Performance Analysis

Timings observed for the system configuration in Figure 3.1 are listed in Table 1. According to our analysis in Section 3.3, the expected $T_d = c_1 + m_1 + d_1 + r_1 + r_2 + r_3 + r_4 = 0.017 + 0.015 + 0.1 + 4^*0.9 = 3.642$ seconds (assuming the scheduled order is c_1, c_2, c_3, and c_4). This value will vary because the system runs under a resource-and-time-sharing environment.

To compare the performance of the distributed configuration and a single-machine system, we also list timings from a SUN4 workstation in Table 1. Thus, $T_s = 0.015 + 0.085 + 4.05 + 4.25 + 4^*0.9 = 12.0$, and we calculate an expected speed-up of $S = 12.0/3.642 = 3.3$.

5 A Computational Electromagnetic Application

5.1 Introduction and Problem Description

Electromagnetic scattering is a widely encountered problem in electromagnetics[8], with important applications in industry such as microwave equipment, radar, antenna, aviation, and electromagnetic compatibility design. Figure 5 illustrates the EMS problem we are modeling, as well as physical parameters tunable by a user. Above an infinite conductor plane, there is an incident EM field in free space. Two slots of equal width on the conducting plane are interconnected to a microwave network behind the plane. The microwave network represents the load of waveguides, for example, a microwave receiver. The incident EM field penetrates the two slots



FIG. 4. *The Graphical User Interface for the option price modeling*

price model/machine	m_k	c_k $(M_I \Rightarrow M_k)$	d_k $(M_k \Rightarrow M_h)$	r_k
BS/DEC5000(M_1)	0.015	0.017	0.1	0.9
AMC/SUN4(M_2)	0.085	0.017	0.1	0.9
EUS/8K DECmpp 12000(M_3)	0.075	0.017	0.1	0.9
EUS/SUN4(M_3)	4.05			
AMS/32-node CM5(M_4)	0.025	0.017	0.1	0.9
AMS/8K DECmpp 12000(M_4)	0.045			
AMS/SUN4(M_4)	4.25			

TABLE 1
Experimental timings for the option price modeling (in seconds)

which are filled with insulation materials such as air or oil. Connected by the microwave network, the EM fields in the two slots interact with each other, creating two equivalent magnetic current sources in the two slots. A new scattered EM field is then formed above the slots. We simulate this phenomena and calculate the strength of the scattered EM field under various physical circumstances. The presence of the two slots and the microwave load in this application requires simulation models with

FIG. 5. *Physical parameters of the EM scattering problem*

In previous work, data parallel and message passing algorithms for this application were developed to run efficiently on massively parallel SIMD machines such as CM-2 and DECmpp-12000, and MIMD machines such as CM-5 and iPSC/860. The data parallel algorithms run approximately about 400 times faster than sequential versions on a high-speed workstation[9]. Parallel models on high performance systems provides a unique opportunity to interactively visualize the EMS simulation in real-time. This problem requires response time of the simulation cycle that is not possible on conventional hardware.

The moment method [8] is used as the numerical model for the EMS problem, which can be represented as:

$$\{\left[\ Y^a\ \right] + \left[\ Y^b\ \right]\}\vec{V} = \vec{I}; \left[\ H\ \right] = \mathcal{L}\{f\ (\vec{V}, \vec{M}, \left[\ H_0^2\ \right])\}$$

where, $\left[\ Y^a\ \right]$: equivalent admittance matrix of the free space; $\left[\ Y^b\ \right]$: equivalent admittance matrix of the microwave network; $\vec{V}$: coefficient vector; $\vec{I}$: the excitation vector; $\vec{M}$: a vector of mode functions; $\left[\ H_0^2\ \right]$: matrix of Hankel functions; f : a

function; $\mathcal{L}$: a linear operator on f; $\left[\ H\ \right]$: final matrix of the simulated EMS field strength.

5.2 System Configuration and Integration

From the previous parallel algorithm design, we observed that:

1. Calculations of $\left[\ Y^a\ \right]$, $\left[\ Y^b\ \right]$, $\vec{I}$, $\vec{M}$, and $\left[\ H_0^2\ \right]$ can be done independently;
2. Computation of $\left[\ Y^a\ \right]$, $\left[\ H_0^2\ \right]$, and the linear solver for $\vec{V}$ have significant communication requirements and are computation intensive;
3. $\left[\ Y^b\ \right]$ is a sparse matrix and calculation of $\vec{M}$ requires little time. Calculation time for $\left[\ Y^a\ \right]$, $\left[\ Y^b\ \right]$ and $\vec{I}$ are relatively balanced.

Thus, we partition computations of this application into four loosely coupled computing modules ('EM-1-SUN', 'EM-2-SUN', 'EM-3-CM5' and 'EM-all-CM5' in Figure 7). 'EM-1-SUN', 'EM-2-SUN', 'EM-3-CM5' can run simultaneously in the distributed computing environment.

At the second level, i.e., data decomposition, because most computations of $\left[\ Y^a\ \right]$, $\vec{V}$(a linear solver), $\left[\ H_0^2\ \right]$, and $\left[\ H\ \right]$ are matrix manipulations, data parallel algorithms are developed in Fortran90 and tailored to run on the CM-5, to take the advantages of CM5's balanced data network and control network. The CM Scientific Subroutine Library is used in the data parallel implementation.

At a more general level, we can view the entire system as an meta-computer that makes use of both functional parallelism and pipelining. In this application, functional parallelism consists of graphical I/O (i.e., user interaction, 3D rendering) and decomposed simulation computations which are handled concurrently by different components of the meta-computer. Pipelining combines calculations and communications among different processors or groups of processor(e.g. the CM5) that are carried out simultaneously in consecutive stages of the simulation.

Figure 6 illustrates the system configuration and module components distributed over the network connecting three high-end workstations and the CM-5. AVS is used to provide sophisticated 3D data visualization and system control functionality required by the simulation.

The home machine is an IBM RS/6000 with a 24-bit color GTO graphics adapter. An AVS coroutine module on the home machine serves as a graphical input and system control interface to monitor and collect user runtime interaction with the simulation through keyboard, mouse and other I/O devices. The AVS kernel runs on another SUN10 server, coordinating data flows and control flows among AVS (remote) modules in the network.

The computation intensive modules of this application are distributed to the CM-5, a MIMD supercomputer which is configured with 32 processing nodes. Two Sun SPARC workstations are used to run the computational modules with modest communication requirements.

FIG. 6. *System configuration for the EMS application*

All modules other than those on the AVS kernel machine are implemented as AVS remote modules. Their input/output ports are defined by specific AVS libraries for receiving/sending data from/to other (remote) modules. This configuration allows the interrupt driven user interface input mechanisms and rendering operations to be relegated to the graphical workstation, while the computation intensive components run on the CM5 coupled with the two workstations. It provides a transparent mechanism for using distributed computing resources along with a sophisticated user interface component that permits a variety of interactive, application-specified inputs.

The graphical user interface shown in Figure 7 includes a main control panel, three individual input panels, and a 3D rendering window. The main control panel provides the user parameters input and simulation control at runtime. There are seven dial widgets representing simulation parameters used by all computing modules on the three remote machines, and a control button for starting a new simulation cycle.

5.3 Performance Analysis

Our experiments show that under a typical working environment (only 0.5 MBits/s of the Ethernet's 10 MBits/s capacity are available), a complete simulation cycle takes about 8 seconds. This response time is quite satisfactory for this application. Table 2 lists timing data of major system components. For comparison, timings of sequential implementation on a SUN4 workstation of the two parallel modules are also given in



FIG. 7. *Graphic user interface for the EMS visualization system*

Module	Calculation time	Comm. time w/ 'Input-interface-IBM	Comm. time w/ 'EM-all-CM5'	Comm. time w/ 'EM-3D-IBM'
EM-1-SUN	0.1(Sun)	0.02	0.045	n/a
EM-2-SUN	0.6(Sun)	0.02	0.5	n/a
EM-3-CM5	1.8(CM5) 1260(Sun)	0.02	0.0	n/a
EM-all-CM5	2.1(CM5) 120(Sun)	n/a	n/a	0.5
Rendering	3.5	n/a	n/a	n/a

TABLE 2
Timings of calculations and communications for the EMS (in second)

the table.

6 A Computational Chemistry Application

6.1 Introduction and Problem Description

Computational chemistry has long been an important user of high-performance computing. Chemistry applications have historically used a significant fraction of

available time on traditional supercomputers. As efficient parallel implementations become increasingly available, usage of massively parallel processors is likewise growing.

The field of computational chemistry includes a variety of methods ranging from $O(n^2)$ in cost (for molecules containing n atoms) to $O(n^4)$ and higher, and generally require memory, I/O, and other resources in accord with their cost. Realistic chemical simulations can involve substantial run times and produce significant amounts of data of interest to the chemist. Visualization of this data most often takes place at the end of the calculation, but because of the length of these calculations, there is an increasing interest in being able to visualize intermediate results as they become available for purposes of computational steering.

In this work, we have integrated a parallel version of the semi-empirical electronic structure package MOPAC [10] into an AVS environment which provides for control of MOPAC's inputs and visualization of intermediate and final results. Our focus is on one of the most common types of calculations using this method, *geometry optimization*, which provides information about energetically stable structures of molecules. These optimized structures are often used as inputs for further calculations. Geometry optimizations of large molecules can be slow to converge and could benefit greatly from the ability to examine intermediate results as the calculation progresses.

6.2 Parallelization of MOPAC

MOPAC is a general-purpose semi-empirical molecular orbital package for the study of chemical structures and reactions. Semi-empirical Hamiltonians are used in the Hartree-Fock [12] method to obtain molecular orbitals, the heat of formation and its derivative with respect to molecular geometry. Using these results MOPAC calculates the vibrational spectra, thermodynamic quantities, isotopic substitution effects and force constrains for a wide range of molecules, including radicals, ions, and polymers. Although MOPAC has been very successfully in many research projects, its application is limited to relatively small molecules, typically consisting of no more than 60 atoms. The limitation comes from the CPU demand that increases with the number of atoms n roughly as $O(n^3)$. A possible solution is to port the code to parallel or distributed computers which is in progress in our laboratory [13].

The structure of MOPAC is described in [10]. Because of the flexibility of the code, *nine* different paths are possible through the code. Central to most of these paths, including the optimization procedures on which we have focused our attention, is the driver routine COMPFG.

We have used three representative test cases to isolate the computation expensive components of the code: retinal (63 atoms), porphin (38 atoms), and tetrabenzene (62 atoms). As shown in Table 3, COMPFG and its descendants account for 99% of the total execution time. Within COMPFG, the primary routines are those involving the two $O(n^3)$ steps in the calculation: DENSIT calculates the electronic density matrix in what amounts to a simplified matrix multiplication and DIAG and HQRII are diagonalization routines. DIAG is, in fact a "fast pseudo-diagonalizer" [11] which takes into account the fact that in most cases, only block diagonalization is required in

Test sets	retinal		porphin		tetrabenz	
	time(sec)	%	time(sec)	%	time(sec)	%
Total CPU time	4817.16	100.0	734.74	100.0	2905.28	100.0
COMPFG CPU time	4791.24	99.5	726.76	98.9	2884.62	99.3
DENSIT CPU time	795.24	16.5	106.49	14.5	469.61	16.2
DIAG CPU time	3090.48	64.2	481.56	65.5	2027.46	69.8
HQRII CPU time	400.97	8.3	12.86	1.8	56.00	1.9
DENSIT+DIAG+HQRII	4286.69	89.0	600.91	81.8	2553.07	87.9

TABLE 3
IBM SP2 timing of kernel subroutines (in second)



FIG. 8. *System configuration of MOPAC*

the Hartree-Fock method. The last column shows that CPU time spent by the three kernel subroutines, DENSIT, DIAG, and HQRII, is more than 80% of total CPU time. Applying the following formula by assuming there are unlimited processors and no communications needed, we can get the theoretical maximum speed-up of 9.1, 5.5, and 8.3 for our test sets.

6.3 System Configuration and Integration

The system can be divided into four parts. Figure 8 shows the system configuration of our MOPAC visualization/computing system.

- **PCH (Parallel Computation Host)** a parallel computer which handles the computation of time-intensive modules (COMPFG in our experiment).

- **SCH (Sequential Computation Host)** a sequential computer which handles file I/O, data distribution, and other sequential modules. It also acts as the coordinator of all computation nodes.



FIG. 9. *The MOPAC graphic interface*

- **AVSH (AVS server)** an AVS server which handles graphic output and controls the execution of modules.

- **XDH (X-windows Display Host)** a color workstation or X-terminal with at least 8-bits pseudo color to display the graphic output.

The PCH is a scalable meta-computer consists of any combination of a SUN4 workstations cluster, an IBM RS6000 cluster, an IBM SP2, and a DEC Alpha Farm. The inter-connection among those computation nodes is a heterogeneous network consists of an Ethernet, an IBM SP2 High Performance Switch, and a DEC Gigaswitch. The MOPAC kernel module is implemented as PVM parallel modules and runs on PCH. It is initiated remotely by the SCH. Although the PCH consists of all the compute nodes physically connected, the actual configuration and number of nodes used can be dynamically determined and modified from the AVS GUI at run time to achieve system load balance and to fit the requirements of input data.

The SCH runs an AVS remote module (*mopacavs*), which is essentially the host program of MOPAC kernel module. It takes the parameters from the AVS control panel. Via the PVM-based heterogeneous network, it handles runtime configuring of the PCH, distributes and initiates PVM node tasks on computation nodes. It also post-processes the results to translate them into AVS graphic calls. The SCH is a high performance workstation in our implementation.

The AVSH can be either a SUN4 or an IBM RS6000. It runs the AVS kernel and handles the communications among remote and local modules. The AVS flow network of MOPAC modules is shown in the right-lower of Figure 9. The input parameters and the configuration of PCH are set through the control panel of module *mopacavs*. Module *atomcntl* controls the display of atom structures. Users can move, zoom, or rotate the atom structures by clicking the bottoms on control panel to get the best view angle of atom structures. The connection between remote and local modules are handled by AVS channels.

	retinal		porphin		tetrabenz	
	Time	Speed-up	Time	Speed-up	Time	Speed-up
$P = 1$	31672	1.00	4869	1.00	19007	1.00
$P = 2$	19222	1.65	3395	1.43	11395	1.67
$P = 4$	16432	1.93	2753	1.77	9059	2.10
$P = 6$	15587	2.03	2539	1.92	8278	2.30

TABLE 4
The SUN4 cluster timing of the test set

6.4 Performance Analysis

The theoretical maximum speed-up of 9.1, 5.5, and 8.3 for our test sets are based on the assumption of unlimited number of processor and no communications. In our present, straightforward parallelization, the first kernel subroutine, DENSIT, requires only one communication to gather results in the end of computation. However, DIAG and HQRII both require numerous small messages during computation. Due to the large amount of communication, we can expect the efficiency of CPU drops sharply when the number of processing node increases, as shown in Table 4

7 Conclusion

The availability of high speed networks, combined with advances in computational power, will support a new set of applications designed for high performance distributed computing. In real world HPCC applications, computational power alone is not sufficient. We see a need for a more broader parallel software engineering environment such as the interactive visualization systems described in this paper, which combines and takes advantage of high performance computing and other well established computing areas such as data visualization, computer graphics, system integration and software engineering. We focus here on an execution model required to combine real-time modeling/simulation, parallel processing, visualization and interactive user control.

With its visual programming interface, modular program structure, dataflow based execution, interactive visualization functionality and its open system characteristics, a process-based integration CASE software like AVS provides an excellent framework to facilitate integration of various system components in a large, multi-disciplinary application, including integration of sophisticated interactive visualization, database management, heterogeneous networking, massively parallel processing and real-time decision making, as well as a useful tool for software development. We believe that with the adoption of HPCC technologies into industry applications, data visualization and software engineering will play an ever-growing important role in technology transfer and parallel software development.

References

[1] Advanced Visual Systems Inc. *AVS 4.0 Developer's Guide and User's Guide*, May 1992.

[2] G. C. Fox, et al, 'InfoVision: Information, Video, Imagery and Simulation on Demand', Technical Report, Syracuse Center for Computational Science SCCS-575, December, 1993.

[3] G. C. Fox, et al, 'InfoMall: A Scalable Organization for the Development of HPCC Software and Systems', Technical Report, Syracuse Center for Computational Science SCCS-531, October, 1993.

[4] K. Mills, M. Vinson, and G. Cheng, 'A Large Scale Comparison of Option Pricing Models with Historical Market Data', Proc. of the *4th Symposium on the Frontiers of Massively Parallel Computation*, Oct. 19-21, 1992, McLean, Virginia.

[5] K. Mills, G. Cheng, M. Vinson, S. Ranka, and G. Fox, 'Software Issues and Performance of a Parallel Model for Stock Option Pricing', Proc. of *the Fifth Australian Supercomputing Conference*, Dec. 6-7, 1992, Melbourne, Australia.

[6] C. Upson, T. Faulhaber, Jr., D. Kamins, D. Laidlaw, D. Schlegel, J. Vroom, R. Gurwitz and A. van Dam, 'The Application Visualization System: A Computational Environment for Scientific Visualization', *IEEE Computer Graphics and Applications*, July, 1989.

[7] Silicon Graphics Inc. *Iris Explorer User's Guide*, 1992.

[8] R. F. Harrington, *Time-Harmonic Electromagnetic Fields*, McGraw-Hill Book Company, New York (1961).

[9] Y. Lu, A. G. Mohamed, G. Fox and R. F. Harrington, 'Implementation of Electromagnetic Scattering from Conductors Containing Loaded Slots on the Connection Machine CM-2', Proc. of *the 6th SIAM Conference on Parallel Processing for Scientific Computing*, March 1993, Norfolk, VA.

[10] Frank J. Seiler Research Laboratory, United States Air Force Academy, CO 80840, *MOPAC Manual*, DEC-3100 edition, December 1990.

[11] J.J.P. Stewart, P. Csaszar, and P. Pulay, 'Fast Semiempirical Calculations'. *Journal of Comp. Chem.*, page pp. 227, 1982.

[12] Atilla Szabo and Neil S. Ostlund, *Modern Quantum Chemistry*, McGraw-Hill, New York, first edition, revised edition, 1989.

[13] T. Haupt, T. Lin and G. Fox, 'Parallelizing MOPAC on distributed computing systems within AVS framework', Technical Report, Syracuse Center for Computational Science, SCCS-744, 1995.

[14] J. Cox, S. Ross, and M. Rubinstein, 'Option Pricing: A Simplified Approach', *Journal of Financial Economics*, Vol. 7, pp. 229-63, 1979.

[15] T. Finucane, 'Binomial Approximations of American Call Option Prices with Stochastic Volatilities', *Journal of Finance*, 1992.

[16] G. Cheng, K. Mills and G. Fox, 'An Interactive Visualization Environment for Financial Modeling on Heterogeneous Computing Systems', in Proc. of *the 6th SIAM Conference on Parallel Processing for Scientific Computing*, R. F. Sincovec, eds., SIAM, Norfolk, VA, March 1993.

[17] G. Cheng, Y. Lu, G.C. Fox, K. Mills and T. Haupt, 'An Interactive Remote Visualization Environment for an Electromagnetic Scattering Simulation on a High Performance Computing System', in Proc. of Supercomputing '93, Portland, OR, November,1993.

[18] G. Cheng, C. Faigle, G. C. Fox, W. Fumanski, B. Li, and K. Mills, 'Exploring AVS for HPDC Software Integration: Case Studies Towards Parallel Support for GIS', Proc.

of *the 2nd AVS Conference AVS'93*, Lake Buena Vista, FL, May 1993.

[19] G. Cheng, G. Fox, K. Mills and M. Podgorny, 'Developing Interactive PVM-based Parallel Programs on Distributed Computing Systems within AVS Framework', Proc. of *the 3rd Annual International AVS Conference, AVS'94*, Boston, MA, May, 1994.

[20] G. Cheng, G. Fox, 'Integrating Multiple Programming Paradigms in a Dataflow-based Software Environment', to be published in *Concurrency Practice and Experience*, John Wiley & Sons Publisher, 1996.

[21] Proc. of *the Pasadena Workshop on System Software and Tools for High Performance Computing Environments*, Pasadena, CA, April 14-16, 1992.

[22] Proc. of *the Workshop and Conference on Grand Challenges Applications and Software Technology*, Pittsburg, Pennsylvania, May 4-7, 1993.

[23] G. Oberbrunner, 'Parallel Networking and Visualization on the Connection Machine CM-5', *the Symposium on High Performance Distributed Computing HPDC-1,September*, 1992, pp. 78-84, Syracuse, NY.

[24] M. F. Krogh and C. D. Hansen, 'Visualization on Massively Parallel Computers using CM/AVS', Proc. of *the 2nd AVS Conference AVS'93*, Lake Buena Vista, FL, May 1993.

[25] G. Oberbrunner, 'MP/Express: Parallel/Distributed Project White Paper', AVS Inc., 1995. http://www.avs.com/techpapers/xp/mp-express/white-paper.html.

[26] A.J. Grant, 'Multiprocessor AVS', Proc. of *the AVS UK Users group conference*, Imperial College, London, 1993.

[27] A. Vaziri, 'Experiences with CM-AVS to Visualize and Compute Simulation Data on the CM-5', Proc. of *the 3rd Annual International AVS Conference, AVS'94*, Boston, MA, May, 1994.

[28] W. Kraske, C. Asano, 'Real Time MPP 3-D Volumetric Visualization: Medical Imaging on the Cray T3D with AVS', *the 4th Annual International AVS Conference, AVS'95*, Boston, MA, April, 1995.

[29] K. Woys, M. Roth, 'AVS Optimization for CRAY Y-MP Vector Processing', *the 4th Annual International AVS Conference, AVS'95*, Boston, MA, April, 1995.

[30] R. Flanery Jr., B. D. Semeraro, 'AVS/EXPRESS and PVM: Gas and Oil National Information Infrastructure (GO-NII) Project', *the 4th Annual International AVS Conference, AVS'95*, Boston, MA, April, 1995.