

Integration of Hand-Held Devices into Collaborative Environments

Geoffrey Fox, Sung-Hoon Ko

Community Grids Laboratory,
Indiana University
gcf@indiana.edu,
suko@indiana.edu
224 Showers Bldg.
501 N. Morton St.
Bloomington, IN 47404
(812) 856 7977
Fax. (812) 856 7972

Kangseok Kim, Sangyoon Oh

Computer Science
Department, Indiana
University
kakim@indiana.edu,
ohsangy@indiana.edu
222 Showers Bldg.
501 N. Morton St.
Bloomington, IN 47404
(812) 856 0751
Fax. (812) 856 7972

Sangmi Lee

Computer Science
Department, Florida State
University
slee@csit.fsu.edu
224 Showers Bldg.
501 N. Morton St.
Bloomington, IN 47404
(812) 856 0750
Fax. (812) 856 7972

Keyword: Collaboration, Mobile, Ubiquitous, Grid, Education

Abstract

We describe a collaborative environment Garnet designed around a universal event model using the publish-subscribe paradigm. We study the integration of personal digital assistants (PDA) into synchronous collaborative sessions. Our architecture uses a PDA adaptor that maps system events into a form suitable for the PDA and uses an optimized protocol that respects bandwidth limitations.

1. Introduction

Universal access refers to the need that all users can access information systems (grids) independent of their access device and their physical capabilities. We address this for personal digital assistants (PDA's) and generalize it to universal collaboration – the capability of multiple users to link together over the web with disparate access modes. Mobile systems are typically slow, unreliable, and have unpredictable temporal characteristics. Further, the user interface is clearly limited. The design of distributed mobile applications needs to identify the practicalities, reliability, and possibilities of continuous interaction and integrate synchronous and asynchronous collaboration.

This paper first describes the basic PDA adaptor architecture. Our production collaboration systems use the Java Message service [25] (JMS) as their publish-subscribe engine and we describe the PDA adaptor that acts as a filter for the PDA of events from JMS. We follow this by a description of some other collaborative functions: the text chat and Instant Messenger tools, and finally the shared display and shared SVG export applications. We are currently doing detailed performance measurements for both PDA and PC clients and expect these to be available in the next month. Fig. 3 includes some initial results without analysis.

Garnet uses core components produced by the Anabas Corporation – a company of which Fox is co-founder. The work described here is independent of this commercial system.

2. Integration Architecture for Garnet and Hand-held device

Garnet Collaboration system [1] is designed to support both centralized and peer-to-peer collaboration models by using a uniform event bus. This event bus is defined in XML (but implemented in a pure Java solution) and supports both control messages and events specifying changes in object state. This is the conventional shared event model of collaboration where such object state messages ensure that objects are properly shared between collaborating clients. Note even shared display (section 4.1) is treated in this fashion with the events specifying changes in the display buffer on the master client. We have built a distributed event broker system Narada [22] that can deliver events either in a deterministic reliable way

like JMS or in the more opportunistic JXTA peer-to-peer [26] model. Narada also interpolates smoothly between these models and would normally be run in a fashion looking like a distributed dynamic set of JMS style event brokers. However all results in this paper come from work using the commercial SonicMQ JMS event broker. The resultant event service is called the Garnet Message service whose XML specification is termed GXOS [23].

An additional characteristic of Garnet collaboration system is heterogeneity of clients. Hand-held devices, mobile phones, as well as conventional desktops can join in one collaboration session. However, the conventional Garnet Message Service

is not able to support lightweight clients, such as Personal Digital Assistants (PDAs) because a lightweight client, mobile clients in most cases, has a smaller display and slower processor. For the integration, we propose a new universal collaboration and access architecture, which we call Garnet Message Service Micro Edition (GMSME). This supports mobile devices and desktop computers. The features of both GMS and GMSME are shown in Table 1. Note that Narada allows a mix of JMS and JXTA like clients with different policies for reliability of message delivery for different subsets of the clients. Thus, one can support a mix of reliable but predetermined interacting PC clients together with multiple JXTA peer groups consisting perhaps of hand-held devices.




Fig 1. PDA adaptor (Personal Server).

Garnet Message Service (GMS)	Garnet Message Service Micro Edition (GMSME)
Conventional Desktop Environment	Lightweight Clients
XML, JMS, P2P	Wireless Communication
Dynamic Routing	Optimized Protocol (HHMS)
Guarantee Delivery	User Status Management

Table 1. GMS and GMSME comparison

GMSME consists of a PDA adaptor, a HHMS protocol (Hand Held Message Service), and an API for application processors, which do message processing of the mobile device application, such as SVG [12,15] or shared export described later. The PDA adaptor sits between mobile clients and the GMS system and does user management, message mapping, connection management, and message optimization based on the user and device specification. The PDA adaptor looks like a typical Garnet client to GMS, and adapts data to the client specifications. For instance, the PDA adaptor ‘listens’ to all the messages and events on the Garnet collaboration system by subscribing to GMS and it delivers messages from the mobile clients to GMS by publishing regular GMS message.

Just as the GMS server deals with message routing [22], the PDA adaptor of GMSME does the same task for mobile devices. Instead of the dynamic message routing server of GMS, the PDA adaptor uses a register table to manage connections and deliver messages. Of course the requirements are different for GMS and GMSME; GMS is coping with dynamic clients linked across the globe; GMSME is focused on a few localized “personal” clients which are however intermittently available and have poor communication links. The mobile user login ID, user ID, is unique over the whole collaboration system. In the GMSME system, the unique user ID is a combination of message destination address, as well as the label of client message processing unit.

HHMS is a natural modification of the event service of GMSME bearing in mind the constraints of hand held devices. The PDA adaptor parses the GMS XML message body and delivers it to the mobile

client over HHMS. As noticed, mobile clients have handicaps in performance and size in comparison with classic desktop machine. Therefore, they require particularly efficient protocols. The HHMS protocol is efficient and not very elaborate. The structure of HHMS is shown in Fig 2. Like GMS, HHMS also sends event and data between software applications. In the HHMS case, software applications are Garnet collaboration system and mobile applications. JMS-based GMS messages contain many properties, such as a destination, a delivery mode, a messageID, which can be extracted from a message header [25], as well as a complex message body. GMSME does not use ‘dynamic routing’ as supported by GMS. Thus, many of GMS message properties are not necessary for GMSME and mobile client. We select the essential fields and map them to a binary message. Consequently, HHMS protocol contains only the necessary data for message delivery in optimized form. Several GMS message fields are implemented in different ways. For instance, the GMS message priority is implemented in GMSME by manipulating a job queue. When an emergency message needs to be delivered, it is just placed at the head of the queue. The PDA adaptor keeps data in the form of a hashtable, to enable priority changes.

GMSME supports heterogeneous clients by customizing message depending on the client specifications. We keep user profile and mobile device profile, such as screen size and device type in the PDA adaptor. As with other objects in the Garnet collaboration system, user profile and device profile use the XML object metadata specification GXOS [23]. As a result, we seamlessly exchange information from the conventional Garnet collaboration system with information on the mobile device. In addition, these profiles make it possible to render messages differently for the mobile client. For example, the shared export update of SVG, PDF, or HTML to a non-color and smaller-size display mobile device can be rescaled and have color modification to provide personalized and optimized look.




Fig 2. Anatomy of a HHMS Message

GMS over JMS	HHMS of GMSME
<i>Publish message</i>	SendHHMS and SendGMS. Mapping the messages between GMS system and mobile clients.
<i>Subscribe message</i>	Register and login
<i>MessageQueue</i>	JobQueue keeps the load inside limits
<i>Recovery</i>	Logfile records major events

Table 2. GMS Message and HHMS

There are some key design issues for GMSME to provide mobile devices the same level of service as desktop computers. We need to achieve ‘optimized performance’, ‘extensible systems’ and ‘robust systems’

Let us consider now performance issues for GMSME, where since the performance of desktop computer exceeds that of mobile device, efficiency is very critical. We accomplish this optimization by two design strategies:

- *Move process to server side*: To reduce process load of mobile device, we move the processing module for each application from the hand held device to the PDA adaptor on the server side. For example, before sending an event message, such as a shared export update, the PDA adaptor performs graphic processing needed for SVG or shared export events. Because of this processing, the mobile client receives a ready to use image from the PDA adaptor.
- *Optimize protocol, HHMS*: HHMS is byte oriented message protocol between mobile client and the PDA adaptor on desktop. Tag bytes in the byte array encode application types, event types, and event message.

We consider two extensibility requirements. The first is a standard interface (API) to the processing module and to the mobile client. All information passing between the PDA adaptor and processing modules uses a *hashtable* object of Java and so additional modules can be easily added. For the communication interface to the mobile client, we have a standard Java interface to deliver byte arrays to and from the PDA adaptor. We currently use HTTP as protocol between the adaptor and its hand held devices.

GMS guarantees message delivery but we adopt a different strategy in GMSME. Garnet identifies “major events” which are those from which one can restart a shared application. Thus, we use a log file listing all major events in the PDA adaptor for each user in GMSME. It allows the PDA adaptor to be able to recover the state of each user from the initial connection or unexpected disconnection from collaboration system. Moreover, we introduce job queue to the PDA adaptor. The job queue in the PDA adaptor keeps the load on mobile device below system limits. This allows us to queue messages that otherwise would exceed available bandwidth and also to send high priority messages by changing message transmission order. Of course, we need fault tolerance approach for PDA adaptor itself. This is delegated to GMS, which guarantees to archive and deliver events. So if an adaptor fails, we switch to an alternative adaptor host, which can restart the PDA collaboration. This could preserve critical information such as adaptor log files as long as the original adaptor publishes these on the GMS publish/subscribe server.

We consider various communication methods between mobile devices and the PDA adaptor. 802.11b wireless LAN [24] is used as an initial communication media but we are also developing support for standard cell phone and PDA data networks. Despite some security issues, 802.11b provides high bandwidth. For cellular phones and most cellular communication using hand held devices, HTTP is the most popular protocol. Because of characteristic pull architecture of the HTTP protocol, we use a polling mechanism to maintain connection with the mobile device. Mobile devices make frequent requests to retrieve messages from the PDA adaptor.

In fig. 3, we present initial results on the performance of GMS and HHMS as a function of message size.




Fig 3. GMS and HHMP Latency.

3. Instant Messenger and Text Chat on PDA

We have integrated PDA based Instant Messenger (IM) and Text Chat into the GMS publish/subscribe collaboration environment. We base this capability on the popular Jabber[21] Open server using XMPP (XML presence protocol) and GMS using the GXOS XML framework for messages. The benefits of using the Jabber Open server include presence management, message processing based on XML, transparent interoperability, structured information data, and open formats. The Jabber server can link to other messenger services like ICQ, MSN, and Yahoo.

The IM on the iPaq PDA was built using "PersonalJava" environment. It




Fig 4. IM and Text Chat Transports

connects first to the PDA adaptor using TCP connection and HHMS protocol. The IM transport shown in fig. 4 runs on the PDA adaptor and establishes a connection to Jabber Open server. Each IM user on iPaq can send messages to other IM users and check online or offline presences of IM users in real time. On the other hand, the Text Chat on iPaq connects to the PDA adaptor in a similar way but now its transport on the adaptor publishes messages to the GMS publish/subscribe server.

We will extend this work to other mobile devices such as cellular phones using J2ME (Java 2, Micro Edition). We can also add SMS (Short Message Service) on mobile devices for sending brief messages between devices like cell phones by using SMS-Jabber Open server currently in the planning phase and SMTP (Simple Mail Transfer Protocol) service on mobile devices for electronic mail used by most email services. In a different project we have already linked SMTP XML (SOAP) transport with GMS publish/subscribe environment. Using SMS transport and SMTP transport to exchange messages between disparate platforms into the PDA adaptor, we can support disparate mobile information devices for universal collaboration and access.

Note that currently we have not integrated the Instant Messenger system into Garnet although this was available in an early prototype. One can either add IM capability to Garnet or modify the Garnet text chat to interact with IM on PDA.

4. Shared applications on PDA

Here we discuss object sharing in real-time with events recording state changes transmitted from a “master” instantiation to replicas on other clients in same session. The documents, includes visualization, web page, Microsoft Word etc. are shared with shared event, shared export or shared display on PDA.

4.1. Shared Display

Shared Display is the simplest method for sharing documents with the frame-buffer corresponding to either a window or entire desktop replicated among the clients. Modest client dependence is possible with PDA’s for example receiving a reduced size image. Some collaboration systems support remote manipulation with user interactions on one machine holding a replica frame-buffer transmitted to the instance holding the original object. This is an important capability in help desk or consulting applications, similar to situations that occur frequently in the debugging of code. As this works for all applications without modifying them, this is the basic shared document mechanism in Garnet System [1]. The public domain *Virtual Network Computing* (VNC) [3] from AT&T Laboratories Cambridge and Microsoft’s *NetMeeting* [4] were two of the earliest popular collaboration systems to implement this capability. Currently, there are several collaborative systems supporting shared display including commercial products; WebEx communication Inc.’s *WebEx* [5], Centra Software Inc.’s *Centra* [6], PlaceWare Inc.’s *PlaceWare* [7], and *Latitude* [8] from Latitude Communication Inc.

Garnet sends GMS events containing an encoded copy of the part of the framebuffer that has been updated. To cope with “late clients” and fault tolerance, major events containing the full frame buffer are sent at regular intervals. The encoding method in Garnet system is adaptive. For instance, if *Huffman* and *LZ77* are requested but the Huffman compressor does not reduce the data, the Huffman request will be skipped and LZ77 will be just processed.

Garnet’s shared display is accessible from small mobile devices through




Fig 5. Architecture of Collaborative Export with SVG

the PDA adaptor that resizes the display for small devices, which have low resolution [2]. The PDA adaptor requests updated data periodically, and optimized data is transferred to PDA with HHMS as raw bitmap data. We developed client application in the PersonalJava runtime environment for Windows CE. This client application is initially designed for Compaq Inc.'s *iPAQ* [9], which has a display resolution of 320 x 240. We are using the Connected Limited Devices Configuration (CLDC) Java Platform [10] to support small wireless devices such as Palm m505 [11] and smart phones. Optimized Raw Bitmap data is encoded to PNG graphic format and wrapped with HHMS protocol to communicate with our initial target – the Palm m505 device that has a resolution of 160 x 160. Shared display for small device needs special optimization because of its limited hardware power and display system. For instance, a traditional shared display system, VNC uses more than 16 blocks for their incremental update. However, the PDAs' low-resolution display system needs fewer blocks to maintain its incremental update, and uses a lighter-weight encoding method.

4.2. Shared Export

Shared display does not allow significant flexibility; for instance, different clients cannot examine separate viewpoints of a scientific visualization. More flexible sharing is possible by sharing object state updates among clients with each client able to choose how to realize the update on its version of the object [1]. This is very time consuming to develop if one must do this separately for each shared application. The shared export model filters the output of each application to one of a set of common formats and builds a custom shared event viewer for these formats. This allows a single collaborative viewer to be leveraged among several different applications. WebEx [5] uses a shared virtual printer that is achieved with shared Acrobat PDF export in Garnet system.

The scalable formats W3C's Scalable Vector Graphics (SVG) [12] and Adobe, Inc.'s Portable Document Format (PDF) [13] are particularly interesting and support of collaborative viewers for them is a major advantage of Garnet System. Scalability implies that each client can resize and scroll while preserving correct positions of pointers and annotations for their various resolutions. SVG is useful as it is already available for Adobe Illustrator [14] and both PowerPoint and Macromedia Flash are exportable to this syntax. Currently there is a Flash (which is a binary 2D vector graphics format) to SVG converter [15] from the University of Nottingham; OpenOffice.org's *OpenOffice* [16] exports PowerPoint to SVG. We would recommend building SVG exports into tools like whiteboards and 2D scientific visualizations to allow convenient interchange among these different 2D presentation tools [1]. W3C's *Annotea* [17] allows similar general collaborative viewers to support collaborative annotation, which is anchoring to objects within the SVG document. Meanwhile, our system supports collaborative annotation at general pixel positions, which are then rendered at appropriate scaled position on each client synchronously.

An exported SVG document is shared by its URI in the Garnet System and the PDA adaptor subscribes to this information. Each PDA adaptor renders the image for various types of wireless devices. We define SVG elements for low-resolution devices with Cascading Style Sheets (CSS) on the PDA adaptor. Display types of small wireless devices are various: from 16bits color with 320x320 resolution [18] to 1 bit gray scale with 160x160 resolution [19]. Every image rendered by PDA adaptor is transferred to each device as a JPEG image format. We have developed the integrated client application for Compaq Inc.'s *iPAQ*, which displays the JPEG image transmitted by HHMS from the PDA adaptor.

The Garnet System provides the interactive framework for collaborative SVG export. As a basic function, our system supports collaborative annotation. Each event for the annotation is translated to SVG document and sent to other participants as a message object with GMS service. The received message is parsed and rendered dynamically. The SVG event processing is based on the W3C document model. Each exported SVG document creates DOM tree, any additional item is added to the DOM tree with DOM interface, and rendered dynamically. Every event message is encoded with XML syntax and delivered to other participants via GMS.

Currently the shared export client is developed for SUN Microsystems Inc.'s *Personal Java* [20] runtime environment and in spite of the universality of Java, we had to take account of the hardware characteristics in each implementation. We are also developing the shared export SVG client for the Palm m505 in a similar fashion to that described for shared display.

References

- [1] G. C. Fox. *Architecture and Implementation of a Collaborative Computing and Education Portal*. ERDC Technical report, May 2001 <http://aspen.ucs.indiana.edu/collabtools/>
- [2] G. C. Fox. *Ubiquitous Access for Computer Science and Education*. ERDC Technical report, May 2001, <http://aspen.ucs.indiana.edu/collabtools/>
- [3] AT&T Laboratories, *VNC - Virtual Network Computing from AT&T Laboratories Cambridge*, <http://www.uk.research.att.com/vnc/>
- [4] Microsoft, Inc. *NetMeeting: Microsoft commercial product description from* <http://www.microsoft.com/netmeeting>
- [5] WebEx Communication, Inc. *WebEx*. <http://www.webex.com>
- [6] Centra Software, Inc. *Centra*. <http://www.centra.com>
- [7] PlaceWare, Inc. *PlaceWare*. <http://www.placeware.com>
- [8] Latitude Communication, Inc. *Latitude*. <http://www.latitude.com>
- [9] Compaq, Inc. *Compaq iPAQ Pocket PC 3765 Detailed Specifications*, <http://athome.compaq.com/showroom/static/iPAQ/3765.asp>
- [10] Sun Microsystems. Connected, *Limited Device Configuration: Java 2 Platform Micro Edition*. Sun Microsystems, version 1.0 edition, May 2000. Available at <http://java.sun.com/products/cldc/>.
- [11] Palm, Inc. *Palm m505 Handheld Product Details*, <http://www.palm.com/products/palmm505/details.html>
- [12] J. Ferraiolo, ed., *Scalable Vector Graphics (SVG) 1.0 Specification*. August 2000. <http://www.w3.org/TR/2000/CR-SVG-20000802/>.
- [13] Adobe Systems, Inc. *Portable Document Format*. <http://www.adobe.com/products/acrobat/adobepdf.html>
- [14] Adobe Systems, Inc. *Adobe Illustrator*. <http://www.adobe.com/products/illustrator/main.html>
- [15] SVG and the Electronic Research Group, *Flash to SVG*, <http://broadway.cs.nott.ac.uk/projects/SVG/#project>
- [16] OpenOffice.org, *OpenOffice*. <http://www.openoffice.org>
- [17] J. Kahan, M. Koivunen, E. Prud'Hommeaux, and R. Swick. *Annotea: An Open RDF Infrastructure for Shared Web Annotations*. In Proc. of the WWW10 International Conference. Hong Kong, 2001.
- [18] Sony, Inc. CLIE Personal Entertainment Organizer Specifications, <http://www.sonystyle.com/micros/ctie/760specifications/PEG-N760C.html>
- [19] Palm, Inc. Palm m500 Handheld Product Details, <http://www.palm.com/products/palmm500/details.html>
- [20] Sun Microsystems Inc. *Personal Java 1.0 Specification*. <http://java.sun.com/products/personaljava/spec-1-0-0/personalJavaSpec.html>
- [21] Jabber Server v1.2 Technical White Paper <http://jabber.org>
- [22] Narada Event Broker Service <http://grids.ucs.indiana.edu/users/shrideep/narada/>
- [23] GXOS <http://aspen.ucs.indiana.edu/~balsoy/gxos/>
- [24] IEEE 802.11b Local Area Network <http://grouper.ieee.org/groups/802/11/>
- [25] "JAVA Message Service" Richard Monson-Haefel and David A Chappell, 2001.
- [26] G. C. Fox, "Peer-To-Peer Networks", *Computing in Science & Engineering*, vol. 3, no 3, May 2001