

Leviton's comprehensive selection of Combination Devices offers lasting durability, convenience and efficiency. Ideal in commercial and residential interiors, they permit installation of two devices in a one-gang space and coordinate beautifully with Decora® and Decora® Plus designer wallplates. Built of impact-resistant thermoplastic construction with double-wipe contacts for maximum conductivity, the devices are UL Listed, CSA and NOM certified.



Combination Devices





DECORA® Combination Devices

Features & Benefits

- Elegant Decora styling provides multiple control in a single-gang wallbox
- All devices have grounding screw
- Fit standard wall boxes

COMBINATION DEVICES 15 AMP

Description	Rating	Cat. No.	Color*
Single-Pole Switch/Receptacle	Switch: 15A-120V AC Receptacle: 15A-125V	5625	I, W, A, GY, E
Single-Pole Switch/Pilot Light	Switch: 15A-120V AC Pilot: 1/25W-125V AC	5626	I, W, A
Two Single-Pole Switches	15A-120/277V AC	5634	I, W, A, GY, E
3-Way Switch/Single-Pole Switch	15A-120/277V AC	5641	I, W, A, E
Two 3-Way Switches	15A-120/277V AC	5643	I, W, A
3-Way Switch/Receptacle	Switch: 15A-120V AC Receptacle: 15A-125V	5645	I, W, A
3-Way Switch/Pilot Light	Switch: 15A-120V AC Pilot: 1/25W-125V	5646	I, W, A
S.P. Switch (Illuminated)/Receptacle	Switch: 15A-120V AC Receptacle: 15A-125V	5647	I, W, A
S.P. Switch (Pilot Light)/Receptacle	Switch: 15A-120V AC Receptacle: 15A-125V	5648	I, W, A

20 AMP

Description	Rating	Cat. No.	Color*
Two Single-Pole Switches	20A-120/277V AC	5627	I, W, A
Single-Pole Switch/Receptacle	Switch: 20A-120V AC Receptacle: 20A-125V	5636	I, W, A
Single-Pole Switch/Pilot Light	Switch: 20A-120V AC Pilot: 1/25W-125V AC	5637	I, W, A
Two 3-Way Switches	20A-120/277V AC	5640	I, W, A

Testing & Code Compliance

- UL Listed (File #E-7458)
- CSA Certified (File #LR-3413)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

Material Characteristics

Environmental: Flammability UL-94, V2 Rating
Operating Temperature: -40°C to 120°C

*Color

Colors available as listed. For color selections, add suffix to catalog numbers as follows:
Ivory (-I), White (-W), Almond (-A), Gray (-GY), Ebony Black (-E).

Horsepower

15 AMP
1/2 @ 120V
2 @ 240V

Dimensional drawings on page T4.

For more information regarding coordinating wallplates, colors, materials, single and multi-gang, refer to Wallplates, section D.



1755-W
in 80301-W

5299-I
in 80401-I

As Seen On



Testing & Code Compliance

Decora Switches

- UL Listed (File #7458)
- CSA (File #LR-3413)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

Switch/GFCI Receptacle

- UL Listed (File #48380)
- Listed UL Standard 943, Class A
- CSA Certified (File #LR-57811)
- NOM Certified (#057)
- Backed by a Limited Two-Year Warranty

Material Characteristics

Environmental: Flammability UL-94, V2 Rating
Operating Temperature: -40°C to 120°C

*Color

Colors available as listed. For other color selections, add suffix to catalog numbers as follows: Ivory (-I), White (-W), Almond (-A).

Dimensional drawings on page T4.

DECORA® Combination Devices

Features & Benefits

- Multi-switch combination devices save space and add convenience
- Common feed shunted internally to all switches
- Elegant Decora styling permits ganging with other Decora devices
- Switch/GFCI Receptacle replaces standard switch/outlet combination devices in commercial or residential installations
- Space-saving GFCI protection in new or retrofit construction
- Switch/GFCI Receptacle permits multiple wiring options that allow six different applications

COMBINATION SWITCHES

Individual Switches: 15AMP 120V/Devices Total: 20 AMP-120V†

Description	Cat. No.	Color*
Dual Rocker Switches	1754	I, W, A
Illuminated Dual Rocker Switches, light is ON when top rocker is off	1754-IL	I, W, A
Three Rocker Switches	1755	I, W, A
Three Rocker Switches (Double Pole ON-OFF-ON Top Switch; Two Single-Pole Switches)	1759	I, W
Dual Rocker Switch with 6" Green Ground Lead	1754-2	I, W
Three Rocker Switch with 6" Green Ground Lead	1755-2	I, W

† WARNING: Although each individual rocker switch is rated up to 15A 120V, the total combined load for both duplex or all three triplex switches MUST NOT EXCEED 20 AMPS.

COMBINATION SWITCH/GFCI OUTLET

Receptacle: 15AMP 125V/Feed-through: 20 AMP 125V Switch

Rating: 8.3 AMP, 1000 WATTS @ 120V AC

Description	Cat. No.	Color* (Basic Cat. No. Denotes Mahogany)
Single-Pole Switch & GFCI-Protected Outlet	5299	I, W, A