ANL/MCS-TM-ANL-96/5

Installation Guide to `mpich`, a Portable Implementation of MPI

by

William Gropp and Ewing Lusk

MATHEMATICS AND
COMPUTER SCIENCE
DIVISION

Contents

Abstract 1

1 Quick Start 1

2 Obtaining and Unpacking the Distribution 2

3 Documentation 4

4 Configuring `mpich` 4
- 4.1 Building a production `mpich` . . . 15
- 4.2 What if there is no Fortran compiler? . . . 15
- 4.3 Special issues for heterogeneous networks . . . 15

5 Compiling `mpich` 15
- 5.1 Getting tcl, tk, and wish . . . 16
- 5.2 Building multiple devices or architectures . . . 16

6 Running an MPI Program 16
- 6.1 Special Considerations for Running on a Network of Workstations . . . 17
  - 6.1.1 Dealing with automounters . . . 18
  - 6.1.2 Faster job startup . . . 19
  - 6.1.3 Stopping the servers . . . 20
  - 6.1.4 Managing the servers . . . 21
- 6.2 Special Considerations for Running with Shared Memory . . . 21

7 Thorough Testing 22

8 Installing `mpich` for Others to Use 23
- 8.1 User commands . . . 23
- 8.2 Installing documentation . . . 24
  - 8.2.1 Man pages . . . 24
  - 8.2.2 Web versions of man pages . . . 24
  - 8.2.3 Examples . . . 25

9 Internationalization 25

10 Benchmarking `mpich` 26

11 The `mpich` Programming Environment 26
- 11.1 Introduction . . . 26
- 11.2 `mpirun`, a Portable Startup Script . . . 27
- 11.3 The `mpicc` and `mpif77` Commands . . . 31
- 11.4 `mpireconfig`, a way to create Makefiles . . . 32
- 11.5 `nupshot`, a Way to View Logfiles . . . 32

12 Automatic Report Generation 32

13 Problems 33

13.1 Submitting bug reports . . . 33
13.2 Problems configuring . . . 34
13.2.1 General . . . 34
13.2.2 LINUX . . . 35
13.3 Problems building `mpich` . . . 36
13.3.1 General . . . 36
13.3.2 Workstation Networks . . . 37
13.3.3 Cray T3D . . . 38
13.3.4 Intel i860 . . . 38
13.3.5 Intel Paragon . . . 38
13.3.6 SGI . . . 39
13.3.7 LINUX . . . 39
13.3.8 IBM SP2 . . . 40
13.3.9 DEC ULTRIX . . . 40
13.4 Problems in testing . . . 41
13.4.1 General . . . 41

Acknowledgments **41**

This *Guide* corresponds to Version 1.1 of `mpich`. It was processed by LaTeX on April 18, 1997.

Abstract

MPI (Message-Passing Interface) is a standard specification for message-passing libraries. `mpich` is a portable implementation of the full MPI specification for a wide variety of parallel computing environments, including workstation clusters and massively parallel processors (MPPs). `mpich` contains, along with the MPI library itself, a programming environment for working with MPI programs. The programming environment includes a portable startup mechanism, several profiling libraries for studying the performance of MPI programs, and an X interface to all of the tools. This guide explains how to compile, test, and install `mpich` and its related tools.

This document describes how to obtain and install `mpich` [7], the portable implementation of the MPI Message-Passing Standard Details on using the MPICH implementation are presented in a separate *User's Guide for* `mpich` [5].

1 Quick Start

Here is a set of steps for setting up and minimally testing `mpich`. Details and instructions for a more thorough tour of `mpich`'s features, including installing, validating, benchmarking, and using the performance evaluation tools, are given in the following sections.

1. If you have `gunzip`, get '`mpich.tar.gz`'; otherwise, get '`mpich.tar.Z`' by anonymous `ftp` from `info.mcs.anl.gov` in the directory `pub/mpi`. (If that file is too big, try getting the pieces from `pub/mpi/mpisplit` and `cat`ing them together.)

2. `gunzip -c mpich.tar | tar xovf -` or `zcat mpich.tar.Z | tar xovf -`

3. `cd mpich`

4. `configure` This will attempt to choose an appropriate default architecture and "device" for you. If the defaults are not what you want, see Section 4

5. `make >& make.log` (in C-shell syntax). This will take awhile; depending on the load on your system and on your file server, it may take anywhere from 10 minutes to an hour or more.

6. (Optional) On workstation networks, or to run on a single workstation, edit the file `mpich/util/machines/machines.sample` to reflect your local host names for your workstations. On parallel machines, this step is not needed. See the `README` file in the `mpich/util/machines` directory for a description of the format. If you skip this step, `configure` will build a default "`machines`" file consisting of multiple entries for the machine that you are configuring on.

7. Build and run a simple test program:

   ```
   cd examples/basic
   make cpi
   mpirun -np 4 cpi
   ```

   At this point you have run an MPI program on your system.

8. (Optional) Put the distribution through its complete acceptance test (See Section 7 for how to do this.

9. (Optional) If you wish to install `mpich` in a public place so that others may use it, use

   ```
   \code{make PREFIX=/usr/local/mpi install}
   ```

   to install `mpich` into '`/usr/local/mpi`', for example. Installation will consist of an `include` and `lib` directory and a small `examples` directory, from which users can copy and modify the `Makefile`. Should you wish to remove the installation, you can run the script `mpiuninstall` in the `bin` directory.

10. (Optional) Build the rest of the MPICH environment: For the `ch_p4` device, use of the secure server (see Section 6.1.2) can speed job startup; you can build it with

    ```
    make serv_p4
    ```

    or

    ```
    make server
    ```

    `server` is a newer version of the secure server that is compatible with `serv_p4`. In addition, it supports the `ch_nexus` device. This version of the server will become the default version in a few more releases.

    The `nupshot` program is a faster version of `upshot`, but requires `tk` source code. If you have this package, you can build `nupshot` with

    ```
    make nupshot
    ```

11. (Optional) At this point you can announce to your users how to compile and run MPI programs, using the installation you have just built in `/usr/local/mpi` (or wherever you have installed it). See Section 11 for commands they can use. They can also copy the `Makefile` in `/usr/local/mpi` and adapt it for their own use.

In the following sections we go through these steps in more detail, and describe other aspects of the `mpich` distribution you might want to explore.

The companion *User's Guide* [5] gives more information on building and running MPI programs with `mpich`.

2 Obtaining and Unpacking the Distribution

`mpich` can be obtained by anonymous `ftp` from the site `info.mcs.anl.gov`. Go to the directory `pub/mpi` and `get` the file `mpich.tar.gz`. This file name is a link to the most recent verstion of `mpich`. Currently it is about 4 Megabytes in size. The file is a `gzip`ped tar file, so it may be unpacked with

```
gunzip -c mpich.tar.gz | tar xvf -
```

If you do not have `gunzip`, but do have `uncompress`, then you must get `mpich.tar.Z` instead, and use either

```
zcat mpich.tar.Z | tar xvf -
```

or

```
uncompress mpich.tar.Z
tar xvf mpich.tar
```

This will create a single directory called `mpich`, containing in various subdirectories the entire distribution, including all of the source code, some documentation (including this *Guide*), `man` pages, the `mpich` environment described in Section 11, and example programs. In particular, you should see the following files and directories:

`COPYRIGHT` Copyright statement. This code is free but not public domain. It is copyrighted by the University of Chicago and Mississippi State University.

`Makefile.in` Template for the '`Makefile`', which will be produced when you run `configure`.

`README` Basic information and instructions for configuring.

`aclocal.m4` Used for building '`configure`' from '`configure.in`'; not needed for most installations.

`bin` Home for executable files like `mpirun` and `mpiman`.

`ccbugs` Directory for programs that test the C compiler during configuration, to make sure that it will be able to compile the system.

`configure` The script that you run to create Makefiles throughout the system.

`configure.in` Input to `autoconf` that produces `configure`.

`doc` Assorted tools for producing documentation, together with this *Installation Guide* and the *User's Guide*.

`examples` Directory containing further directories of example MPI programs. Of particular note are `basic`, with a few small examples to try first, `test`, with a test suite for exercising `mpich`, and `perftest`, containing benchmarking code.

`include` The include libraries, both user and system.

`lib` The machine-dependent libraries, after they are built. Subdirectories are maintained for each version of the system that is built, so this same tree can be host for multiple installations. Machine-dependent scripts such as `mpirun` and `mpireconfig` are also kept here.

`man` Man pages for `MPI`, `MPE`, and internal routines.

`mpe` The source code for the `MPE` extensions for logging and X graphics. The `contrib` directory contains examples. Best are the `mandel` and `mastermind` subdirectories.

`mpid` The source code for the various "devices" that customize `mpich` for a particular machine, operating system, and environment.

`profiling` The profiling subsystem, including a system for automatically generating the "wrappers" for the MPI profiling interface.

`ref` Contains Postscript versions of the `man` pages.

`src` The source code for the portable part of `mpich`. There are subdirectories for the various parts of the MPI specification.

`util` Utility programs and files.

If you have problems, check the `mpich` home page on the Web at `http://www.mcs.anl.gov/Projects/mpi/mpich` . This page has pointers to lists of known bugs and patchfiles. If you don't find what you need here, send mail to `mpi-bugs@mcs.anl.gov`.

3 Documentation

This distribution of `mpich` comes with complete `man` pages for the MPI routines, the MPE extensions, and the ADI (Abstract Device Interface) routines. The command `mpiman` in `mpich/bin` is a good interface to the man pages.[1] The `mpich/ref` directory contains printable versions of the man pages for MPI and the ADI, in compressed PostScript form. The `mpich/doc` directory contains this *Installation Guide* and also the *User's Guide*.

4 Configuring `mpich`

The next step is to configure `mpich` for your particular computing environment. `mpich` can be built for a variety of parallel computers and also for networks of workstations. Parallel computers supported include the IBM SP1 and SP2 (using various communication options), the TMC CM-5, the Intel Paragon, IPSC860, and Touchstone Delta, the Ncube Ncube2, the Meiko CS-2, the Kendall Square KSR-1 and KSR-2, Convex Exemplar, and IBM, SGI and Sun Multiprocessors. Workstations supported are the Sun4 family, Hewlett-Packard, DEC 3000 and Alpha, IBM RS/6000 family, and SGI. Also supported are Intel x86-based PC clones running the LINUX or FreeBSD operating systems. New ports are always pending.

Configuration of `mpich` is done with the `configure` script contained in the top-level directory. This script is automatically generated by the Gnu `autoconf` program from the file `configure.in`, but you do not need to have `autoconf` yourself.

The configure script documents itself in the following way. If you type

[1] The `mpiman` command is created by the configure process described later.

```
configure -usage
```

you will get a complete list of arguments and their meanings. So the simplest way to document the options for `configure` is to just show its output here:

```
Configuring with args -usage
Configuring MPICH Version 1.1.0.
Usage: /home/MPI/mpich/configure [-arch=ARCH_TYPE] [-comm=COMM_TYPE]
            [-device=DEVICE]
            [-prefix=INSTALL_DIR]  [-c++[=C++_COMPILER]]
            [-cc=C_COMPILER] [-fc=FORTRAN_COMPILER]
            [-clinker=C_LINKER] [-flinker=FORTRAN_LINKER]
            [-c++linker=CC_LINKER]
            [-mpe] [-nompe] [-nof77] [-f90nag] [-opt=OPTFLAGS]
            [-make=MAKEPGM]
            [-cflags=CFLAGS] [-fflags=FFLAGS] [-c++flags=CCFLAGS]
            [-optcc=C_OPTFLAGS] [-optf77=F77_OPTFLAGS]
            [-lib=LIBRARY] [-mpilibname=MPINAME]
            [-no_mpegraphics] [-no_short_longs] [-memdebug]
            [-x11_lib=X11LIB] [-x11_inc=X11INC]
            [-mpedbg] [-nompedbg] [-cross] [-devdebug] [-nodevdebug]
            [-debug] [-nodebug] [-tracing]
            [-var_pkt] [-pkt_size=LENGTH] [-adi_collective]
            [-adi_coll_world]
            [-wish=WISH] [-tcldir=TCLDIR] [-tkdir=TKDIR]
            [-fortnames=FORTRANNAMES]
            [-ar_nolocal] [-automountfix=AUTOMOUNTFIX]
            [-noranlib] [-rsh=RSHCOMMAND] [-rshnol]
            [-nexusthreads] [-nexusdir=NEXUSDIR] [-nexuslib=NEXUSLIB]
            [-nexusdebug]
where
   ARCH_TYPE    = the type of machine that MPI is to be configured for
   COMM_TYPE    = communications layer or option to be used
   DEVICE       = communications device to be used
   INSTALL_DIR  = directory where MPI will be installed (optional)
   C++_COMPILER = default is to use g++ (optional)
   OPTFLAGS     = optimization flags to give the compilers (e.g. -g)
   CFLAGS       = flags to give C compiler
   FFLAGS       = flags to give Fortran compiler
   MAKEPGM      = version of make to use
   LENGTH       = Length of message at which ADI switches from short
                  to long message protocol
   WISH         = Name of tcl/tk wish executable.  Configure will attempt
                  to find a version of wish for you, but if there is
                  no wish in your path or you need to use a different
                  version, use this option.  Used only for the display
                  tools (nupshot and upshot).  tk 3.x required for nupshot;
                  tk 3.x or 4.x for upshot.
```

```
   TCLDIR       = Directory containing tcl.  Must have lib/libtcl.a and
                  include/tcl.h .  Used only for nupshot.
   TKDIR        = Directory containing tk 3.3, 3.4, 3.5, or 3.6.  Must have
                  lib/libtk.a and include/tk.h .  Used only for nupshot.
                  May be the same as TCLDIR.
   FORTRANNAMES = Form of the Fortran names.  See below.
   X11LIB       = Full path name for libX11.a
   X11INC       = Full path name for X11.h
   AUTOMOUNTFIX = Command to fix automounters
   RSHCOMMAND   = Command to use for remote shell
   MPILIBNAME   = Name to use instead of mpi in the name of the MPI
                  library.  If set, libMPILIBNAME will be used instead
                  or libmpi.  This can be used on systems with
                  several different MPI implementations.
   NEXUSDIR     = the location of the nexus distribution
   NEXUSLIB     = the location of the nexus library, if not in the standard
                  place within the distribution

All arguments are optional, but if 'arch', 'comm', or 'prefix' arguments
are provided, there must be only one.  'arch' must be specified before
'comm' if they both appear.

If '-c++' is included as an option, then the C++ interface is also built.
By default, g++ is used as the c++ compiler.  THIS IS CURRENTLY
UNSUPPORTED.

You can select a different C and Fortran compiler by using the '-cc' and
'fc' switches.  The environment variables 'CC' and 'FC' can also provide
values for these but their settings may be overridden by the configure
script.  Using '-cc=$CC -fc=$FC' will force configure to use those
compilers.

If '-cross' is given, configure assumes that you are cross-compiling.  If
it is not given, configure expects to be able to run programs.  Even if
'-cross' is not selected, configure will try to determine if you are
cross-compiling; this switch is needed only on systems where attempting
to run a cross-compiled program causes the configure script to hang.

If '-mpe' is included as an option, then the MPE 'helper' libraries will
also be built.  '-nompe' causes the MPE libraries to not be built.  The
default is '-mpe'.  If '-no_mpegraphics' is used, then the MPE routines
that make use of X11 graphics will NOT be built; this is appropriate for
systems that either do not have the X11 include files or that do not
support X11 graphics (some message-passing systems cannot interoperate
with X11).  The options -x11_inc and -x11_lib may be used to specify the
locations of the X11 include files and libraries in the event that
configure cannot find them (they should both be specified in that case).
```

The option '-mpedbg' enables the '-mpedbg' command line switch in MPI programs. When used with an MPI program, the default error handler (i.e., MPI_COMM_WORLD's error handler) tries to start xterm's running dbx for each process that detects an error. This option is intended primarily for workstation environments but should work on some MPPs (such as IBM SP2).

The option '-nof77' prevents the compilation of routines that require a Fortran compiler. If this option is selected, you may not use the Fortran interface to MPI.

The option '-f90nag' allows you to use the NAG Fortran 90 instead of Fortran 77. This is a preliminary version and is based on the version for NeXTs.

The option '-opt' allows you to specify optimization options for the compilers (both C and Fortran). For example, '-opt=-O' chooses optimized code generation on many systems. '-optcc' and '-optf77' allow you to specify options for just the C or Fortran compilers. Use -cflags and -fflags for options not related to optimization.

The option '-nexusthreads' enables multithreading within the ch_nexus device. The default version of the ch_nexus device is configured as single-threaded.

The option '-nexusdebug' enables special debugging services in the ch_nexus device. The default version of the ch_nexus device is configured without debugging.

The option '-nexusdir=NEXUSDIR' allows one to specify the location of an installed version of Nexus. The default is to use a version that is distributed with MPICH, in the mpid/ch_nexus directory.

The option '-nexuslib=NEXUSLIB' allows one to specify a specific nexus library to link against. The default is -lnexus_dl. Note that this is not a path name.

The option '-lib' allows you to specify the location of a library that may be needed by a particular device. Most devices do NOT need this option; check the installation instructions for those that might.

The option '-make' may be used to select an alternate make program. For example, on FreeBSD systems, -make=gnumake may be required because of bugs in the system make.

The option '-no_short_longs' may be used to suppress support for ANSI C types 'long long int' and 'long double' when they are the same size as 'long' and 'double' respectively. Some systems allow these long ANSI C

types, but generate a warning message when they are used; this option may be used to suppress these messages (and support for these types).

The option '-fortnames=FORTRANNAMES' allows you to specify the form of the Fortran names. This is used primarily to generate names with and without trailing underscores for those systems that support both. Possible values are

FORTRANNAMES value	if Fortran MPI_SEND looks like
DOUBLEUNDERSCORE	mpi_send__
UNDERSCORE	mpi_send_
CAPS	MPI_SEND
NOUNDERSCORE	mpi_send

This option should normally NOT be used; configure determines what the Fortran compiler generates. This can be used to override that choice.

The option '-ar_nolocal' prevents the library archive command from attempting to use the local directory for temporary space. This option should be used when (a) there isn't much space (less than 20 MB) available in the partition where MPICH resides and (b) there is enough space in /tmp (or wherever ar places temporary files by default).

The option '-noranlib' causes the 'ranlib' step (needed on some systems to build an object library) to be skipped. This is particularly useful on systems where 'ranlib' is optional (allowed but not needed; because it is allowed, configure chooses to use it just in case) but can fail (some 'ranlib's are implemented as scripts using 'ar'; if they don't use the local directory, they can fail (destroying the library in the process) if the temporary directory (usually '/tmp') does not have enough space. This has occured on some OSF systems.

The option '-memdebug' enables extensive internal memory debugging code. This should be used only if you are trying to find a memory problem (it can be used to help find memory problems in user code as well).

The option '-debug' enables the collection of additional information for parallel debuggers such as Totalview.

The option '-tracing' enables tracing of internal calls. This should be used only for debugging the MPICH implementation itself.

The option '-rsh' allows you to select an alternative remote shell command (by default, configure will use 'rsh' or 'remsh' from your 'PATH'). If your remote shell command does not support the '-l' option (some AFS versions of 'rsh' have this bug), also give the option '-rshnol'. These options are useful only when building a network version of MPICH (e.g., '-device=ch_p4' or '-device=ch_tcp').

Special Tuning Options:

There are a number of options for tuning the behavoir of the ADI (Abstract Device Interface) which is the low-level message-passing interface. These should NOT be used unless you are sure you know what you are doing.

The option '-nodevdebug' disables the debugging code in the MPI ADI code. This should be used only when you are sure that everything is working correctly. (This option is also present to remind benchmarkers that the low level code by default may contain debugging code.) Note also that some of the device code (in mpid/*) has had the debugging code removed from the source code. '-devdebug' turns on the debugging code. '-nodevdebug' is the default.

The option '-var_pkt' allows you to set the message size at which MPICH changes from its short to long message protocol.

The option '-pkt_size=LENGTH' allows you to choose the message length at which the ADI (Abstract Device Interface) switches from its short to long message format. LENGTH must be positive.

The option '-adi_collective' allows the ADI to provide some collective operations in addition to the basic point-to-point operations. Currently, most systems do not support this option (it is ignored) and on the others it has not been extensively tested. The option '-adi_coll_world' asks the ADI to try and use any collective operations that are supported only on the MPI_COMM_WORLD communicator (and any communicator with a similiar group). This is also untested.

Sample Configure Usage:

To make for running on sun4's running SunOS with ch_p4 as the device, and with the installation directory equal to the current directory:

```
./configure -device=ch_p4 -arch=sun4
make
```

Known devices are

```
        ch_nx     (native Intel NX calls),
        ch_mpl    (native IBM EUI or MPL calls),
        ch_p4     (p4)
        ch_nexus  (Nexus)
        ch_meiko  (for Meiko CS2, using NX compatibility library),
        ch_shmem  (for shared memory systems, such as SMPs),
        ch_lfshmem(for shared memory systems, such as SMPs; uses
                   lock-free message buffers),
```

```
        ch_cenju3 (native NEC Cenju-3 calls)

The following devices were supported with ADI-1, but are currently
unsupported.  Please contact us if you are interested in helping us
support these devices:
        meiko     (for Meiko CS2, using elan tport library), and
        nx        (for Intel Paragon),
        t3d          (for the Cray T3D, using Cray shmem library).
        ch_nc     (native nCUBE calls, requires -arch=ncube),
        ch_cmmd   (native TMC CM-5 CMMD calls),

Known architectures include (case is important)
        sun4      (SUN OS 4.x)
        solaris   (Solaris)
        solaris86 (Solaris on Intel platforms)
        hpux      (HP UX)
        rs6000    (AIX for IBM RS6000)
        sgi       (Silicon Graphics IRIX 4.x, 5.x or 6.x)
        sgi5      (Silicon Graphics IRIX 5.x on R4400's, for the MESHINE)
        IRIX      (synonym for sgi)
        IRIX32    (IRIX with 32bit objects -32)
        IRIXN32   (IRIX with -n32)
        IRIX64    (IRIX with 64bit objects)
        alpha     (DEC alpha)
        intelnx   (Intel i860 or Intel Delta)
        paragon   (Intel Paragon)
        meiko     (Meiko CS2)
        CRAY      (CRAY XMP, YMP, C90, J90, T90)
        cray_t3d  (CRAY T3D)
        freebsd   (PC clones running FreeBSD)
        LINUX     (PC clones running LINUX)
        ksr       (Kendall Square KSR1 and KSR2)
        EWS_UX_V  (NEC EWS4800/360AD Series workstation.  Untested.)
        UXPM      (UXP/M. Untested.)
        uxpv      (uxp/v. Untested.)
        SX_4_float0
                  (NEC SX-4; Floating point format float0
                             Conforms IEEE 754 standard.
                   C:       sizeof (int)     = 4; sizeof (float) = 4
                   FORTRAN: sizeof (INTEGER) = 4; sizeof (REAL)  = 4)
        SX_4_float1
                  (NEC SX-4; Floating point format float1
                             IBM floating point format.
                   C:       sizeof (int)     = 4; sizeof (float) = 4
                   FORTRAN: sizeof (INTEGER) = 4; sizeof (REAL)  = 4)
        SX_4_float2
                  (NEC SX-4; Floating point format float2
                             CRAY floating point format.
```

```
                C:       sizeof (int)     = 4; sizeof (float) = 8
                FORTRAN: sizeof (INTEGER) = 8; sizeof (REAL)  = 8)
                !!! WARNING !!! This version will not run
                                together with FORTRAN routines.
                                sizeof (INTEGER) != sizeof (int)
        SX_4_float2_int64
                (NEC SX-4; Floating point format float2 and
                           64-bit int's)
                 C:       sizeof (int)     = 8; sizeof (float) = 8
                 FORTRAN: sizeof (INTEGER) = 8; sizeof (REAL)  = 8)

Special notes:

For SGI (-arch=IRIX) multiprocessors running the ch_p4 device, use
-comm=ch_p4 to disable the use of the shared-memory p4 communication
device, and -comm=shared to enable the shared-memory p4 communication
device.  The default is to enable the shared-memory communication device.

Others may be recognized.
```

Normally, you should use `configure` with as few arguments as you can. For example, setting the C compiler with `-cc=xxx` may require also setting `-cflags=yyy`; configure will (usually) choose both the compiler and flags appropriately. If you leave all arguments off, `configure` will usually guess the correct architecture (`arch`) unless you are in a cross-compiling environment, and will usually choose an appropriate device (`device`) as well. Where TCP/IP is an appropriate mechanism for communication, the TCP device (`ch_p4`) will be chosen by default.

`mpich` is implemented using an abstract device specification (ADI), described in [3]. In some environments, this abstract device is configured to be the native communication subsystem of the machine. This is done with the `device` argument to `configure`. For the rest of the environments, a generic communication device is constructed using `p4` [1, 2] and that is used as the instantiation of the ADI. In these cases, use `ch_p4` as the device.

The `ARCH_TYPE` specifies what kind of processor the compilations will take place on. Valid ones are listed above. For the IBM SP, the architecture type is `rs6000`. If not given, `configure` will attempt to determine the type.

Some machines have multiple communication options, which are specified with the `comm` argument. Currently, the `ch_p4` device makes use of this. By selecting `-comm=shared`, a version of the `ch_p4` device that permits the use of both shared memory and IP/TCP is built. This is particularly useful on clusters of symmetric multiprocessors.

A new device (`ch_nexus`, based on the Nexus run-time system is currently available, although not yet thoroughly tested. Like the `ch_p4` device, the Nexus device is able to use multimethod communication on some platforms. For example, the IBM SP binary can communicate via MPL or TCP depending on which node it is communicating with. See http://www.mcs.anl.gov/nexus for more details.

Some sample invocations of `configure` are shown below. In most cases, the `mpe` libraries

are also built (See *User's Guide*). To build without the `mpe` libraries, configure with `-nompe`. In many case, the detailed invocations below are the defaults, which you would get if you invoked `configure` with no arguments.

First, for massively parallel processors (MPPs) and multiprocessors:

Convex Exemplar For a Convex Exemplar, please get the official version from Convex/HP. This is based on MPICH, but has been tuned for better performance on the Exemplar. If for some reason you want to use the shared memory version of MPICH on the Convex, use

```
configure -device=ch_shmem -arch=hpux
```

Cray multiprocessor (not a CRAY T3D but, for example, a 4 processor Cray YMP or C90)

```
configure -device=ch_p4 -arch=CRAY
```

Cray t3d (assuming you are logged into the YMP front end).

```
configure -device=t3d -arch=cray_t3d
```

Because the T3D is cross-compiled, you should make sure that your `PATH` variable contains the directory with the T3D tools. We have seen '`/mpp/bin`' and '`/opt/ctl/bin`'; check with your system administrator for the paths that you should have when building T3D applications. Make sure that this path is at the head of your path list.

Intel Paragon `configure -device=ch_nx -arch=paragon`

IBM SP2 (using the high-performance switch for communication)

```
configure -device=ch_mpl -arch=rs6000
```

To use this you must have POE installed. Note, however, that this works only for POE versions *without* a native MPI. If you do have IBM's native MPI, then you can try the following (this is untested)

```
cd include
ln -s /usr/lpp/ppe.poe/include/mpproto.h mpproto.h
cd ..
configure -arch=rs6000 -device=ch_mpl -opt="-03 -qarch=pwr2"  \
          -cc=cc -clinker=mpcc -f77=xlf -flinker=mpxlf \
          -make=/usr/local/bin/gnumake -mpilibname=mpich
make
```

This is unsupported; if you have suggestions for improving these instructions, please let us know.

Meiko CS-2 `configure -device=ch_meiko -arch=meiko`

SGI multiprocessors such as the Power Challenge and Origin 2000.

```
configure -device=ch_shmem
```

If you need to generate a particular version that corresponds to the `-32`, `-n32`, or `-64` compiler/linker options on SGI, use the architectures `IRIX32`, `IRIXN32`, or `IRIX64` respectively instead of SGI. Specifically, use the following for an R10000 SGI:

```
configure -arch=IRIX64 \
    -cc="cc -64 -mips4 -r10000" \
    -fc="f77 -64 -mips4 -r10000" \
    -opt="-O2" \
    -device=ch_shmem

configure -arch=IRIXN32 \
    -cc="cc -n32 -mips4 -r10000" \
    -fc="f77 -n32 -mips4 -r10000" \
    -opt="-O2" \
    -device=ch_shmem

configure -arch=IRIX32 \
    -cc="cc -32" \
    -fc="f77 -32" \
    -opt="-O2" \
    -device=ch_shmem
```

(The optimization level is optional; -O2 has worked for some users. Be careful of aggressive optimization, particularly in the '`mpid/ch_shmem`' code.)

See the comments under SGI workstations for different 32 and 64 bit options.

For networks of workstations (can interoperate with other types of workstations),

DEC Alpha In order to get the full advantages of ANSI C, you may need to add `-cflags="-std"`. For strict ANSI C, use `-cflags="-std1"`.

IBM RS6000 In order to get the advantages of ANSI C, you may need to add `-cflags="-qlanglvl=ansi"`. The MPICH code uses `__STDC__` to check for the presence of ANSI C features; the IBM RS6000 compilers do *not* define this by default.

SGI `configure -device=ch_p4`

Some SGI systems support both 32 and 64 bit pointers (addresses). MPICH uses the architecture `IRIX` to refer to 32 bit systems and `IRIX64` for 64 bit systems. You can use `-arch=IRIX` or `-arch=IRIX64` to force a particular system. If you need to generate a particular version that corresponds to the `-32`, `-n32`, or `-64` compiler/linker options on SGI, use the architectures `IRIX32`, `IRIXN32`, or `IRIX64` respectively instead of `sgi`.

SGI multiprocessor (such as an Onyx, Challenge, or Power Challenge), using the shared memory for fast message-passing

```
configure -device=ch_p4 -comm=shared
```

Use `-arch=IRIX` to force 32 bit pointers and `-arch=IRIX64` to force 64 bit pointers.

On the SGI Origin machines, it is better to let configure choose the architecture and to attach the flags to the compilers and linker as follows:

```
configure -cc='cc -64' -fc='f77 -64'  ....
```

Sun SunOS including the `mpe` libraries (See the Users Guide [5]:

```
configure -device=ch_p4 -arch=sun4 -mpe
```

Sun Solaris `configure -device=ch_p4 -arch=solaris -mpe`

DEC Alpha `configure -device=ch_p4 -arch=alpha`

FreeBSD For a network of PC's running the FreeBSD version of Unix:

```
configure -device=ch_p4 -arch=freebsd
```

Nexus device For a machine using the Nexus device, change the device in the above examples to `ch_nexus`. The Nexus device requires an ANSI C compiler, because the Nexus header files use the function prototypes. If the default compiler is does not support function prototypes (assuming ansicc is your compiler), add `-cc=ansicc` to the configure command line. Remember to point this at the correct compiler for your message passing system (e.g., `mpcc` for the SP, or `icc` for the Paragon).

You may need to set the environment variables `NEXUS_INCLUDE_DIR` and `NEXUS_LIB_DIR` to indicate the directories containing the Nexus include files and libraries respectively. Do this before running configure.

HP HPUX For a network of HP's, including the `mpe` library but leaving out of it the MPE X graphics routines:

```
configure -device=ch_p4 -arch=hpux -mpe -no_mpegraphics
```

Fujitsu For a network of Fujitsu M780s running UXP/M, the following options have been tested:

```
setenv FC frt
configure -arch=UXPM -device=ch_p4 -fflags="-Oe,-Uep -Eml -Aabe" \
    -mpe -mpedbg -prefix=/usr/local/mpi \
    -tcldir=/usr/local -tkdir=/usr/local -wish=/usr/local/bin/wish
```

NEC SX-4 For an NEC SX-4 shared-memory vector multiprocessor, use

```
configure -device-lfshmem
```

to get the lock-free shared-memory device described in [6].

`mpich` can be run on a heterogeneous network of workstations of various kinds. For simple collections of workstations, the `mpirun` command can be used; more complex collections of heterogeneous machines require a `p4` "procgroup file" (for the `ch_p4` device) or a "startup file" (for the `ch_nexus` device). The format of these files is described in Section 6.1.

4.1 Building a production mpich

By default, configure sets up mpich to be compiled without optimization and with additional code to help in identifying problems and behaviour of the mpich implementation. Once mpich passes the tests (see Section 7), you may wish to rebuild mpich without the debugging code. This will produce significantly smaller libraries and slightly faster code. To do this, add the options

```
-opt=-O -nodevdebug
```

to the configure line, and re-run make. You may also include multiple optimization options by inclosing them in quotes:

```
-opt="-O -qarch=pwr2"
```

4.2 What if there is no Fortran compiler?

The configure program should discover that there is no Fortran compiler. You can force configure to not build the Fortran parts of the code with the option -nof77. In this case, only the C programs will be built and tested.

4.3 Special issues for heterogeneous networks

When building MPICH for a heterogeneous collection of workstations, you may want to configure with the option -no_short_longs. This indicates to MPICH that it should not provide support for the C type long double. This can improve performance between systems that have the same datatype lengths for all other types (some Intel x86 machines have 12 byte long doubles; many other systems use either 8 or 16 byte long doubles).

5 Compiling mpich

Once configure has determined the features of your system, all we have to do now is

```
make
```

This will clean all the directories of previous object files (if any), compile both profiling and non-profiling versions of the source code, build all necessary libraries, and link both a sample Fortran program and a sample C program as a test that everything is working. If anything goes wrong, check Section 13 to see if there is anything said there about your problem. If not, follow the directions in Section 13.1 for submitting a bug report. To simplify checking for problems, it is a good idea to use

```
make >& make.log &
```

Specific (non-default) targets can also be made. See the `Makefile` to see what they are.

After running this `make`, the size of the distribution will be about 20 Megabytes (depending on the particular machine it is being compiled for), before building any of the examples or the extensive test library. The `Makefile`s are built for the various example subdirectories, but the example programs themselves have to be made "by hand".

5.1 Getting tcl, tk, and wish

These software packages are available by anonymous ftp from `ftp.smli.com` in directory '`/pub/tcl`'. They are needed only for the `upshot` and `nupshot` programs; you do not need them in order to install MPI.

You should get `tcl7.3.tar.Z` and `tk3.6.tar.Z` (and patch `tk3.6p1.patch`). Later versions of both tcl and tk are incompatible with these and do not work with `nupshot`. The `upshot` program has been modified to work with either tk 3.6 or tk4.0.

It is necessary that the `wish` program be accessible to users; the other parts of tcl and tk do not need to be installed (but make sure that everything that `wish` itself needs is installed).

5.2 Building multiple devices or architectures

When building more than one version of MPICH, it is important to use the versions of the programs `mpirun` etc. from the library directory, not '`mpich/bin`'.

6 Running an MPI Program

In order to make running programs on parallel machines nearly as portable as writing them, the environment distributed with `mpich` contains a script for doing so. It is the `mpirun` command, found in the `mpich/bin` directory. Several of the examples directories already have symbolic links to this command, but eventually you might want to add it to your path, with (assuming your shell is the C shell)

```
set path=($path /home/me/mpich/bin)
```

More details on `mpirun` can be found in Section 11.2. If you are going to run on a network of workstations, you will need a `machines.xxxx` file in `mpich/util/machines`; see Section 6.1 for details. Systems that use various kinds of filesystem automounters may need to make small changes to these programs; these are detailed in Section 6.1.1.

Some simple MPI programs will have been built during the compilation process. They are in the directory `mpich/examples/basic` and contain a C and a Fortran program for estimating π. So change to that directory and do

```
mpirun -np 4 cpi
```

to run the C version, and

```
mpirun -np 4 fpi
```

to run the Fortran version. At this point, you have minimally tested your installation of `mpich`. You might also want to check out the performance of MPI on your system. You can do a crude check by running the program `systest`, also found in the `examples/basic` directory. To try it, do:

```
make systest
mpirun -np 2 systest
```

For a more precise benchmark, see Section 10.

Another program in the `examples/basic` subdirectory is `cpilog`. This program uses some of the routines from the MPE library; you must have configured with the `-mpe` option. If you make it and run it, it will produce a simple log file that can be viewed with the program analysis tool `upshot`. To do so, you may need to build `upshot` with

```
make upshot
```

in the top level MPICH directory. Note that `upshot` requires the tk shell `wish`. To use `upshot` to view a log file, do

```
make cpilog
mpirun -np 4 cpilog
upshot cpilog.log
```

The log file produced by `cpilog` is not very interesting, since `cpi` is such a simple program. Many interesting logfiles can be found in the `profiling/upshot/logfiles` subdirectory. The file `cpilog.c` demonstrates how to instrument your own code for producing such logs. The Users guide [5] describes how to link with a version of `mpich` that produces them automatically. For a short description of the programs in the `examples/basic` directory, see the `README` file there. The logging routines are part of `mpe`, so be sure that your configuration has been done with the `-mpe` option.

6.1 Special Considerations for Running on a Network of Workstations

To run on a network of workstations, you must specify in some way the host names of the machines that you want to run on. This can be done in several ways. These are described in detail in the *Users Guide*. We give a shorter version here.

The easiest way is to edit the file `mpich/util/machines/machines.xxxx`, to contain names of machines of architecture `xxxx`. The `xxxx` matches the `arch` given when `mpich` was configured. Then whenever `mpirun` is executed, the required number of hosts will be selcted from this file for the run. (There is no fancy scheduling; the hosts are selected starting from the top). To run all your MPI processes on a single workstation, just make all the lines in the file the same. A sample `machines.sun4` file might look like:

```
mercury
venus
earth
mars
earth
mars
```

To run the test suite in `examples/test`, you need a machines file with at least five lines in it. This is for homogeneous networks. Heterogeneous networks are discussed in the *Users' Guide*.

6.1.1 Dealing with automounters

Automounters are programs that dynamically make file systems available when needed. While this is very convenient, many automounters are unable to recognize the file system names that the automounter itself generates. For example, if a user accesses a file '`/home/me`', the automounter may discover that it needs to mount this file system, and does so in '`/tmp_mnt/home/me`'. Unfortunately, if the automounter on a different system is presented with '`/tmp_mnt/home/me`' instead of '`/home/me`', it may not be able to find the file system. This would not be such a problem if commands like `pwd` returned '`/home/me`' instead of '`/tmp_mnt/home/me`'; unfortunately, it is all too easy to get a path that the automounter should, but does not, recognize.

To deal with this problem, `configure` allows you to specify a filter program when you configure with the option `-automountfix=PROGRAM`, where `PROGRAM` is a filter that reads a file path from standard input, makes any changes necessary, and writes the output to standard output. `mpirun` uses this program to By default, the value of `PROGRAM` is

```
sed -e s@/tmp_mnt/@/@g
```

This uses the `sed` command to strip the string `/tmp_mnt` from the file name. Simple `sed` scripts like this may be used as long as they do not involve quotes (single or double) or use `%` (these will interfere with the shell commands in configure that do the replacements). If you need more complex processing, use a separate shell script or program.

As another example, some systems will generate paths like

```
/a/thishost/root/home/username/....
```

which are valid only on the machine `thishost`, but also have paths of the form

```
/u/home/username/....
```

that are valid everywhere. For this case, the configure option

```
-automountfix='sed -e s@/a/.\*/home@/u/home@g'
```

will make sure that `mpirun` gets the proper filename.

6.1.2 Faster job startup

When using the `ch_p4` or `ch_nexus` devices, it is possible to speedup the process of starting jobs by using the *secure server*. The secure server is a program that runs on the machines listed in the '`machines.ARCH`' file and that allows programs to start faster. There are two ways to install this program: so that only one user may use it and so all users may use it. No special privileges are required to install the secure server for a single user's use.

To use the secure server, follow these steps:

1. Choose a *port*. This is a number that you will use to identify the secure server (different port numbers may be used to allow multiple secure servers to operate). A good choice is a number over 1000. If you pick a number that is already being used, the server will exit, and you'll have to pick another number. On many systems, you can use the `rpcinfo` command to find out which ports are in use (or reserved). For example, to find the ports in use on host `mysun`, try

   ```
   rpcinfo -p mysun
   ```

2. If using the `ch_p4` device, build the secure server. From the top level directory, do

   ```
   make serv_p4
   ```

   At the end of this step, the executable for the secure server is in the same directory as the MPI libraries. The name of the server is `serv_p4`.

   Alternately, do

   ```
   make server
   ```

   from the top level directory. At the end of this step, the new secure servier is in the same directory as the MPI libraries. The name of the server is `server`.

3. Start the secure server. The script '`bin/chp4_servs`'

   ```
   bin/chp4_servs -port=n -arch=$ARCH
   ```

   can be used to start the secure servers. This makes use of the remote shell command (`rsh` or `remsh`) to start the servers; if you can not use the remote shell command, you will need to log into each system on which you want to start the secure server and start the server manually. The command to start an individual server using port `2345` is

   ```
   serv_p4 -o -p 2345 &
   ```

   For example, if you had choosen a port number of 2345 and were using `sun4`s, then you would give the command

   ```
   bin/chp4_servs -port=2345 -arch=sun4
   ```

The server will keep a log of its activities in a file with the name '`P4Server.Log.xxxx`' in the current directory, where '`xxxx`' is the process id of the process that started the server (note that the server may be running as a child of that initial process).

The newer server uses the file '`Secure_Server.Log.xxxx`'.

4. To make use of the secure servers using the `ch_p4` device, you must inform `mpirun` of the port number. You can do this in two ways. The first is to give the `-p4ssport n` option to `mpirun`. For example, if the port is `2345` and you want to run `cpi` on four processors, use

```
mpirun -np 4 -p4ssport 2345 cpi
```

   The other way to inform `mpirun` of the secure server is to use the environment variables `MPI_USEP4SSPORT` and `MPI_P4SSPORT`. In the C-shell, you can set these with

```
setenv MPI_USEP4SSPORT yes
setenv MPI_P4SSPORT 2345
```

   The value of `MPI_P4SSPORT` must be the port with which you started the secure servers. When these environment variables are set, no extra options are needed with `mpirun`.

5. If using the `ch_nexus` device, find the Nexus secure server in the Nexus directory, for example, '`/usr/local/nexus/bin/sserver`'.

6. Start the Nexus secure server on each machine. The command to start an individual server using port `2345` is

```
ssserver -d -p 2345 &
```

7. The `ch_nexus` device requires that you record the port numbers in a resource database ('`.rdb`') file. The format of the file is

```
<host> ss_port=<port #>
```

   The `-nexusdb` flag should be used to tell mpirun the name of the file:

```
mpirun -nexusdb ports program
```

Note that when MPICH is installed, the secure server and the startup commands are copiedinto the library directory so that users may start their own copies of the server. This is discussed in the Users Guide.

6.1.3 Stopping the servers

To stop the servers, their processes must be killed. This is easily done with the Scalable Unix Tools [4] with the command

```
pfps -all -tn serv_p4 -and -o $LOGNAME -kill INT
```

Alternately, you can log into each system and execute something like

```
ps auxww | egrep '$LOGNAME.*serv_p4'
```

and then use the `kill` command on the resulting process number (users of System V-style `ps` commands will have to figure out what their particular form of `ps` needs and adjust the `egrep` command accordingly).

An alternative approach is discussed in Section 6.1.4

6.1.4 Managing the servers

An experimental `perl5` program is provided to help you manage the p4 secure servers. This program is `chkserv`, and is in the `util` directory. You can use this program to check that your servers are running, start up new servers, or stop servers that are running.

Before using this script, you *must* edit it. It has sample values for the fields that it will use. In particular, you should set `serv_p4`, `portnum`, and `machinelist` appropriately; you may also need to set the first line to your version of `perl5`.

To check on the status of your servers, use

```
chkserv -port 2345
```

To restart any servers that have stopped, use

```
chkserv -port 2345 -restart
```

This does not restart servers that are already running; you can use this as a `cron` job every morning to make sure that your servers are running. Note that this uses `rsh` to start the process on the remote systems; if you can't use `rsh`, you'll need to restart the servers by hand. In that case, you can use the output from `chkserv -port 1234` to see which servers need to be restarted.

```
chkserv -port 2345 -kill
```

This contacts all running servers and tells them to exit. It does not use `rsh`, and can be used on any system (it contacts the server and tells it to exit).

This software is experimental. If you have comments or suggestions, please send them `mpibugs@mcs.anl.gov`.

6.2 Special Considerations for Running with Shared Memory

When using the `ch_shmem` or `ch_lfshmem` devices with System V shared memory, processes that exit abnormally (e.g., with a segmentation violation) may leave System V semaphores

or shared memory segments allocated[2] Since there is usually a limited number of these objects, it is important to recover them. The Unix command `ipcs` can be used to list the allocated semaphores and shared memory segments, and `ipcrm` can be used to delete them. The script '`bin/cleanipcs`' can be used to identify and delete *all* System V IPCs owned by the calling user; the use is simply

```
bin/cleanipcs
```

7 Thorough Testing

The `examples/test` directory contains subdirectories of small programs that systematically test a large subset of the MPI functions. The command

```
make testing
```

in the `mpich/examples/test` directory will cause these programs to be compiled, linked, executed, and their output to be compared with the expected output. Linking all these test programs takes up considerable space, so you might want to do

```
make clean
```

in the test directory afterwards. The individual parts of MPI (point-to-point, collective, topology, etc.) can be tested separately by

```
make testing
```

in the separate subdirectories for `examples/test`.

If your disk space is limited, consider either running with

```
make testing TESTARGS=-small
```

or by going to each directory and executing

```
./runtests -small
```

With the `-small` switch, each executable is built, run, and deleted before the next test program is built.

If you have a problem, first check the troubleshooting guides and the lists of known problems. If you still need help, send detailed information to `mpi-bugs@mcs.anl.gov`.

[2]Surprisingly, the System V IPC (interprocess communication) mechanisms do not have a "delete on unreferenced" attribute.

8 Installing mpich for Others to Use

This step is optional. Once you have tested all parts of the MPI distribution (including the tools, particularly upshot and/or nupshot), you may install mpich into a publically available directory, and disseminate information for other users, so that everyone can use the shared installation. To install the libraries and include files in a publicly available place, choose a directory, such as /usr/local/mpi, change to the top-level mpich directory, and do

```
make install PREFIX=/usr/local/mpi
```

The man pages will have been copied with the installation, so you might want to add /usr/local/mpi/man to the default system MANPATH. The man pages can be conveniently browsed with the mpiman command, found in the mpich/bin directory.

A good way to handle multiple releases of mpich is to install them into directories whose names include the version number and then set a link from mpi to that directory. For example, if the current version is 1.0.13, the installation commands to install into '/usr/local' are

```
make install PREFIX=/usr/local/mpi-1.0.13
rm /usr/local/mpi
ln -s /usr/local/mpi-1.0.13 /usr/local/mpi
```

The script 'util/mpiinstall' provides more control over the installation of MPICH (in fact, make install just runs this script). For example, you can change the protection of the files when they are installed with the options -mode=nnnn (for regular files) and -xmode=nnnn (for executables and directories). You can set the directory into which the man pages will be placed with -manpath=<path>. The option -help shows the full set of options for mpiinstall.

Installing nupshot can sometimes be troublesome. You can use the switch -nonupshot to mpiinstall to not install nupshot; alternately, you can use the switch -cpnuphost to install the copy in 'mpich/profiling/nupshot'. Normally, mpiinstall builds a new version of nupshot to insure that all of the paths are correct (nupshot needs to find files where it is installed). If you need to "manually" build nupshot for installation, the -cpnupshot switch will allow you to install that version.

If you are supporting multiple devices on a single platform (for example, ch_p4 and ch_shmem), you should build one and install it in the regular way, then build the second and install it with mpiinstall -libonly. In this case, make sure that your users use the programs in the library directory rather than the 'bin' directory.

8.1 User commands

The commands mpirun, mpicc, mpif77, mpiman, and mpireconfig should be in the user's search path. Note that if several architectures and/or MPICH devices are supported, it is important that the correct directory be added to the user's path. For convenience, these

are in both '`mpich/bin`' and '`mpich/lib/<arch>/<device>`'; if there is any chance that multiple architecures or devices are used, the second form should be used.

8.2 Installing documentation

The MPICH implementation comes with several kinds of documentation. Installers are encouraged to provide site-specific information, such as the location of the installation (particularly if it is not in '`/usr/local/mpi`').

8.2.1 Man pages

A complete set of Unix man pages for the MPICH implementation are in '`mpich/man`'. '`man/man3`' contains the MPI routines; '`man/man4`' contains the MPE routines and `mpirun`, and '`man/man5`' contains the MPID routines (these are for the low-level part of the MPICH implementation, are are not of interest to users). The command '`mpich/bin/mpiman`' is a script that runs `xman` on these man pages.

8.2.2 Web versions of man pages

Web (HTML) versions are available from ftp://info.mcs.anl.gov/pub/mpi/manwww.tar.Z. They are available at http://www.mcs.anl.gov/mpi/www. A sample Web page is shown below, and is also available in '`mpich/util/mpichsite.html`'

```
<TITLE>Using MPICH at Argonne</TITLE>

<H1>Site-specific information on the MPICH implementation of MPI</H1>

<H2>Location of libraries</H2>
The MPICH implementation is located in <TT>/usr/local/mpi/lib</TT>; the
libraries are in
<DL>
<DT> <TT>lib/sun4/ch_p4</TT>
<DD> for Sun4

<DT> <TT>lib/rs6000/ch_mpl</TT>
<DD> for the SPx

<DT> <TT>lib/IRIX/ch_shmem</TT>
<DD> for the SGI system
</DL>

<H2>Location of programs</H2>
Programs are located in the same directory as the libraries

<H2>Documentation</H2>
The command <TT>/usr/local/mpi/bin/mpiman</TT> provides man pages with xman.
The <A HREF="http://www.mcs.anl.gov/mpi/www/index.html">man pages</A>
```

```
are also available.  The
<A HREF="http://www.mcs.anl.gov/mpi/mpi-report-1.1/mpi-report.html">MPI
Standard Version 1.1</A> is available in hypertext form.

<H2>Examples</H2>
A simple example in C and Fortran is in <TT>/usr/local/mpi/examples</TT>.
More examples may be found in the MPICH source tree, located at
<TT>/home/MPI/mpich/examples</TT>.
```

8.2.3 Examples

Users often prefer working from example '`Makefile`'s and programs. The directory that is installed in the '`examples`' directory contains a C and Fortran version of the 'pi' program, along with a '`Makefile.in`'. Users may be interested in some of the examples that are in the source tree, also in the '`examples`' directory.

9 Internationalization

`Mpich` has support for providing error messages in different languages. This makes use of the X/Open message catalog services, which are a standard way of providing multi-language support. This multi-language support is often called NLS, for National Language Support. `Mpich` comes with error messages in US English; additional languages will be provided as we get the translations (if you wish to provide one, please send mail to `mpi-bugs@mcs.anl.gov`). More precisely, `mpich` uses an English version that uses the ISO Latin-1 character set (ISO8859-1). We expect to provide other versions that also use the Latin-1 character set, subject to getting translations of the messages.

To create a new message catalog, copy the file '`mpich.En_US.msg`' to a file '`mpich.mylanguage.msg`' and translate the entries. The value of '`mylanguage`' should match the ones used for your system; for example, '`mpich.De_DE.msg`' for German. Many systems put their NLS files in '`/usr/lib/nls/msg`'; you can also check the value of the environment variable `NLSPATH` on your system. Note that some systems provide the routines and programs to support NLS, but do not make use of it and do not provide a initial `NLSPATH` value.

For emacs users, check the Emacs info under "European Display". The commands

```
M-x standard-display-european
M-x iso-accents-mode
```

can be used to input most European languages. You can also load '`iso-transl`' and use `C-x 8` to compose characters (this sets the high bit in the character). `Mpich` currently does not support languages that require multi-byte character sets (such as Japanese). However, the only changes needed are in the file '`src/env/errmsg.c`'; if you are interested in developing a multi-byte character set version, please let us know.

By default, mpich uses the value of 'NLSPATH' to find the message catalogs. If this fails, it tries 'MPICHNLSPATH', and if that fails, it uses English language versions that are coded into the library.

The catalogs are not, however, installed into these directories. Instead, you will find them in the library directory for a particular architecture; for example, 'mpich/lib/rs6000'.

10 Benchmarking mpich

The mpich/examples/perftest directory contains a sophisticated tool for measuring latency and bandwidth for mpich on your system. To run it, first make sure that mpich was configured with the -mpe option. Then go to mpich/examples/perftest and do

```
make
mpirun -np 2 mpptest -gnuplot > out.gpl
```

The file out.gpl will then contain the necessary gnuplot commands. The file mppout.gpl will contain the data. To view the data with gnuplot, use:

```
gnuplot out.gpl
```

or use

```
load 'out.gpl'
```

from within gnuplot. Depending on your environment and version of gnuplot, you may need to start gnuplot first and issue the command set terminal x11 before executing load 'out.gpl'.

The programs mpptest and goptest have a wide variety of capabilities; the option -help will list them. For example, mpptest can automatically pick message lengths to discover any sudden changes in behavior and can investigate the ability to overlap communication with computation. These programs are written using MPI, and may be used with *any* MPI implementation, not just MPICH.

11 The mpich Programming Environment

11.1 Introduction

The MPI standard specifies nothing outside of MPI programs, not even how they will be started. MPICH supplies a number useful tools for managing MPI programs, including

1. mpirun, a portable startup command, so that MPI programs can be started the same way in many different environments,
2. mpicc and mpif77, easy ways to compile and link MPI programs.

3. `mpireconfig`, a way to create Makefiles from Makefile.in templates

4. `mpe`, a library of useful routines that work will with MPI. Curently this library includes both routines for producing log files of time-stamped events and a simple parallel X graphics library, routines for providing a sequential section code, and routines to start a debugger when errors occur.

5. a set of predefined profiling libraries. The MPI Standard specifies a mechanism whereby the user may "wrap" any collection of MPI functions with code of his own, without accessing the MPI implementation source code. We supply tools for constructing such a profiling version of the MPI library with a minimum of effort, as well as three preconstructed sets of wrappers, for accumulating time spent in MPI routines, for preparing log files, and for program animation.

6. `upshot`, a tool for examining log files produced by the `mpe` logging functions or by the automatic logging in the logging profiling library.

7. `nupshot`, an experimental, faster version of `upshot`.

11.2 `mpirun`, a Portable Startup Script

Each parallel computing environment provides some mechanism for starting parallel programs. Unfortunately, these mechanisms are very different from one another. In an effort to make this aspect of parallel programming portable as well, `mpich` contains a script called `mpirun`. this is script is partially customized during the configuration process when `mpich` is built. Therefore the actual "source" for `mpirun` is in the file `mpirun.sh.in` in the `mpich/bin` directory. The most common invocation of `mpirun` just specifies the number of processes and the program to run:

```
mpirun -np 4 cpi
```

the complete list of options for `mpirun` is obtained by running

```
mpirun -help
```

This is the result:

```
mpirun [mpirun_options...] <progname> [options...]

  mpirun_options:
    -arch <architecture>
            specify the architecture (must have matching machines.<arch>
            file in /homes/gropp/mpich/bin/machines) if using the execer
    -h      This help
    -machine <machine name>
            use startup procedure for <machine name>
            Currently supported:
              chameleon
              meiko
```

```
          paragon
          p4
          sp1
          ibmspx
          anlspx
          ksr
          sgi_mp
          ipsc860
          inteldelta
          cray_t3d
          execer
          smp
          symm_ptx

-machinefile <machine-file name>
        Take the list of possible machines to run on from the
        file <machine-file name>.  This is a list of all available
        machines; use -np <np> to request a specific number of machines.
-np <np>
        specify the number of processors to run on
-nolocal
        don't run on the local machine (only works for
        p4 and ch_p4 jobs)
-stdin filename
        Use filename as the standard input for the program.  This
        is needed for programs that must be run as batch jobs, such
        as some IBM SP systems and Intel Paragons using NQS (see
        -paragontype below).
-t      Testing - do not actually run, just print what would be
        executed
-v      Verbose - throw in some comments
-dbx    Start the first process under dbx where possible
-gdb    Start the first process under gdb where possible
         (on the Meiko, selecting either -dbx or -gdb starts prun
         under totalview instead)
-xxgdb  Start the first process under xxgdb where possible (-xdbx
        does not work)
-tv     Start under totalview
-ksq    Keep the send queue. This is useful if you expect later
        to attach totalview to the running (or deadlocked) job, and
        want to see the send queues. (Normally they are not maintained
        in a way which is visible to the debugger).

  Special Options for NEC - CENJU-3:

-batch  Excecute program as a batch job (using cjbr)

-stdout filename
```

```
        Use filename as the standard output for the program.
-stderr filename
        Use filename as the standard error  for the program.

-jid    Jobid from Job-Scheduler EASY.
        If this option is specified, mpirun directly executes
        the parallel program using this jobid.
        Otherwise, mpirun requests np nodes from the Job-Scheduler
                   in interactive or batch mode.
                   In interactive mode (i.e. option -batch is not
                   specified), mpirun waits until the processors are
                   allocated, executes the parallel program and
                   releases the processors.


  Special Options for Nexus device:

-nexuspg filename
        Use the given Nexus startup file instead of creating one.
        Overrides -np and -nolocal, selects -leave_pg.

-nexusdb filename
        Use the given Nexus resource database.

Special Options for Workstation Clusters:

-e      Use execer to start the program on workstation
        clusters
-pg     Use a procgroup file to start the p4 programs, not execer
        (default)
-leave_pg
        Don't delete the P4 procgroup file after running
-p4pg filename
        Use the given p4 procgroup file instead of creating one.
        Overrides -np and -nolocal, selects -leave_pg.
-tcppg filename
        Use the given tcp procgroup file instead of creating one.
        Overrides -np and -nolocal, selects -leave_pg.
-p4ssport num
        Use the p4 secure server with port number num to start the
        programs.  If num is 0, use the value of the
        environment variable MPI_P4SSPORT.  Using the server can
        speed up process startup.  If MPI_USEP4SSPORT as well as
        MPI_P4SSPORT are set, then that has the effect of giving
        mpirun the -p4ssport 0 parameters.

Special Options for Batch Environments:
```

```
-mvhome Move the executable to the home directory.  This
        is needed when all file systems are not cross-mounted
        Currently only used by anlspx
-mvback files
        Move the indicated files back to the current directory.
        Needed only when using -mvhome; has no effect otherwise.
-maxtime min
        Maximum job run time in minutes.  Currently used only
        by anlspx.  Default value is 15 minutes.
-nopoll Do not use a polling-mode communication.
        Available only on IBM SPx.
-mem value
       This is the per node memory request (in Mbytes).  Needed for some
       CM-5s. ( Default 32. )

-cpu time
       This is the the hard cpu limit used for some CM-5s in
       minutes. (Default 15 minutes.)

Special Options for IBM SP2:

-cac name
        CAC for ANL scheduler.  Currently used only by anlspx.
        If not provided will choose some valid CAC.

Special Options for Intel Paragon:

-paragontype name
       Selects one of default, mkpart, NQS, depending on how you want
       to submit jobs to a Paragon.

-paragonname name
       Remote shells to name to run the job (using the -sz method) on
       a Paragon.

-paragonpn name
       Name of partition to run on in a Paragon (using the -pn name
       command-line argument)
```

On exit, mpirun returns a status of zero unless mpirun detected a problem, in which case it returns a non-zero status (currently, all are one, but this may change in the future).

Multiple architectures may be handled by giving multiple -arch and -np arguments. For example, to run a program on 2 sun4s and 3 rs6000s, with the local machine being a sun4, use

```
/home/MPI/mpich/util/mpirun -arch sun4 -np 2 -arch rs6000 -np 3 program
```

```
This assumes that program will run on both architectures.  If different
executables are needed, the string '%a' will be replaced with the arch name.
For example, if the programs are program.sun4 and program.rs6000, then the
command is

    /home/MPI/mpich/util/mpirun -arch sun4 -np 2 -arch rs6000 -np 3 program.%a

If instead the executables are in different directories; for example,
/tmp/me/sun4 and /tmp/me/rs6000, then the command is

    /home/MPI/mpich/util/mpirun -arch sun4 -np 2 -arch rs6000 -np 3 /tmp/me/%a/program

It is important to specify the architecture with -arch BEFORE specifying
the number of processors.  Also, the FIRST -arch command must refer to the
processor on which the job will be started.  Specifically, if -nolocal is
NOT specified, then the first -arch must refer to the processor from which
mpirun is running.
```

For backward compatibility with earlier versions of `mpirun`, each of these arguments can also be used with the prefix `mr_`, as in

```
mpirun -mr_np 4 myprog
```

11.3 The `mpicc` and `mpif77` Commands

The `mpich` implementation provides two commands for compiling and linking C and Fortran programs. You may use these commands *instead of* the '`Makefile.in`' versions, particularly for programs contained in a small number of files. In addition, they have a simple interface to the profiling and visualization libraries described in [9]. This is a program to compile or link MPI programs. In addition, the following special options are supported:

-mpilog Build version that generates MPE log files.

-mpitrace Build version that generates traces.

-mpianim Build version that generates real-time animation.

-show Show the commands that would be used without actually running them.

Use this just like the usual C or Fortran compiler. For example,

```
mpicc -c foo.c
mpif77 -c foo.f
```

and

```
mpicc -o foo foo.o
mpif77 -o foo foo.o
```

Commands for the linker may include additional libraries. For example, to use some routines from the MPE library, enter

```
mpicc -o foo foo.o -lmpe
```

Combining compilation and linking in a single command, as shown here,

```
mpicc -o foo foo.c
mpif77 -o foo foo.f
```

may not work on some systems, and is not recommended.

These commands are set up for a specific architecture and MPICH device and are located in the directory that contains the MPI libraries. For example, if the architecture is `sun4` and the device is `ch_p4`, these commands may be found in '`/usr/local/mpi/lib/sun4/ch_p4`' (assuming that MPICH is installed in '`/usr/local/mpi`').

11.4 `mpireconfig`, a way to create Makefiles

Much of MPICH's portability is handled throught the careful construction of system-dependant Makefiles by the `configure` program. This is fine for installing MPICH, but what can you do when you are building a new application? For simple applications, the `mpicc` and `mpif77` commands may be the simplest way to build a new application. For more complex codes, we recommend taking a sample '`Makefile.in`' file, for example, in '`mpich/examples/test/pt2pt`'. Modify those parts that are are relavent, such as the `EXECS` and specific program targets. To create a Makefile, just execute

```
mpireconfig Makefile
```

(`mpireconfig` is in the same directory as `mpirun`). This generates a new Makefile from Makefile.in, with the correct parameters for the MPICH that was installed.

11.5 `nupshot`, a Way to View Logfiles

`Nupshot` is a newer version of `upshot` [8] and can display log files created by using either the `-mpilog` option to `mpicc` or `mpif77` or through use of the MPE logfile facilities.

12 Automatic Report Generation

We are working on a prototype system for automatically producing a report describing the installation of MPI on the system you are using. This is done by going to the top-level directory and doing

```
configure ... >& config.log
doc/port
```

Warning: this rebuilds the system, since one of the things the report will contain is the set of machine-specific parameters used and the total time it take to build it. The reason for directing the configure output to a file is so that the document generator can include comments on the configuration itself, such as calling out any problems that `configure` noticed.

If the system that you are running on contains all the necessary components for producing the report, it will appear in the file `doc/doc1.tex`. This is a LaTeX file and should be processed in the '`doc`' directory:

```
cd doc
latex doc1
bibtex
latex doc1
dvips doc1
```

The graphs of performance require `gnuplot` and are generated as Postscript files.

13 Problems

This section describes some commonly encountered problems and their solutions. It also describes machine-dependent considerations. You should also check the Users Guide, where problems related to compiling, linking, and running MPI programs (as opposed to building the MPICH implementation) are discussed.

13.1 Submitting bug reports

Any problem that you can't solve by checking this section should be sent to `mpi-bugs@mcs.anl.gov`. Please include:

- The version of MPICH (e.g., 1.0.13)
- The output of running your program with the `-mpiversion` argument (e.g., `mpirun -np 1 a.out -mpiversion`)
- The output of

  ```
  uname -a
  ```

  for your system. If you are on an SGI system, also

  ```
  hinv
  ```

- If the problem is with a script like configure or mpirun, run the script with the `-echo` argument (e.g., `mpirun -echo -np 4 a.out`)
- If you are using a network of workstations, also send the output of `bin/tstmachines`. The program `tstmachines` is discussed in the Users Guide.

If you have more than one problem, please send them in separate messages; this simplifies our handling of problem reports.

The rest of this section contains some information on trouble-shooting MPICH. Some of these describe problems that are peculiar to some environments and give suggested work-arounds. Each section is organized in question and answer format, with questions that relate to more than one environment (workstation, operating system, etc.) first, followed by questions that are specific to a particular environment. Problems with workstation clusters are collected together as well.

13.2 Problems configuring

13.2.1 General

1. **Q:** When trying to run `configure`, I get error messages like

   ```
   ./configure: syntax error at line 20: `(' unexpected
   ```

   A: You have an obsolete version of the Bourne shell (`sh`). MPICH requires that the `sh` shell support shell procedures; this has been standard in most Bourne shells for years. To fix this, you might consider (a) getting an update from your vendor or (b) installing one of the many publically available sh-shell replacements.

2. **Q:** The configure reports the compiler as being broken, but there is no problem with the compiler (it runs the test that supposedly failed without trouble).

   A: You may me using the Bash shell ('`/bin/bash`') as a replacement for the Bourne shell ('`/bin/sh`'). We have reports that, at least under LINUX, Bash does not properly handle return codes in expressions. One fix is to use a different shell, such as '`/bin/ash`', on those systems.

   This won't work on some LINUX systems (*every* shell is broken). We have reports that the following will work:

   (a) In '`configure`', change `trap 'rm -f confdefs*' 0` to
   `trap 'rm -f confdefs*' 1`

   (b) After configure finishes, remove the file '`confdefs.h`' manually.

3. **Q:** configure reports errors of the form

   ```
   checking gnumake... 1: Bad file number
   ```

   A: Some versions of the `bash` shell do not handle output redirection correctly. Either upgrade your version of `bash` or run configure under another shell (such as `/bin/sh`). Make sure that the version of `sh` that you use is not an alias for `bash`. `configure` trys to detect this situation and will normally issue an error message.

4. **Q:** Configure reports that floating point is not commutative! How do I fix it?

   A: Check your compiler's documentation. On RS/6000's, the `-qnomaf` (no multiply-add floating point) option. On some other systems, intermediate results may be stored in 80-bit registers (Intel CPUs do this); this can also lead to inconsistent rounding. You may be able to force the compiler to round to 64 bits.

13.2.2 LINUX

1. **Q:** The configure step issues the message:

   ```
   checking that the compiler f77 runs... no
   Fortran compiler returned non-zero return code
   Output from test was
   f2ctmp_conftest.f:
      MAIN main:
   ```

   A: This is probably caused by a problem in the Fortran compiler in LINUX. The `f77` command in LINUX is often a shell script that uses the `f2c` program to convert the Fortran program to C, and then compile it with the C compiler. In many versions of LINUX, this script has an error that causes a non-zero return code even when the compilation is successful.

   To fix this problem, you need a corrected `f77` script. If you can edit the script yourself, change the last 3 lines from

   ```
   case $cOPT in 2) $CC $G -o $OUTF $OFILES -lf2c -lm;; esac
   rc=$?
   exit $rc
   ```

   to

   ```
   case $cOPT in 2) $CC $G -o $OUTF $OFILES -lf2c -lm;; esac
   rc=$?
   trap 0
   exit $rc
   ```

2. **Q:** The link test fails on LINUX with messages like

   ```
   overtake.o(.text+0x59): undefined reference to `MPI_COMM_WORLD'
   overtake.o(.text+0x81): undefined reference to `MPI_COMM_WORLD'
   ...
   ```

   A: This is probably caused by a problem in the Fortran compiler in LINUX. The `f77` command in LINUX is often a shell script that uses the `f2c` program to convert the Fortran program to C, and then compile it with the C compiler. In many versions of LINUX, this script has an error that causes a non-zero return code even when the compilation is successful.

   To fix this problem, you need a corrected `f77` script. If you can edit the script yourself, change the last 3 lines from

```
case $cOPT in 2) $CC $G -o $OUTF $OFILES -lf2c -lm;; esac
rc=$?
exit $rc
```

to

```
case $cOPT in 2) $CC $G -o $OUTF $OFILES -lf2c -lm;; esac
rc=$?
trap 0
exit $rc
```

13.3 Problems building `mpich`

13.3.1 General

1. **Q:** When running make on `mpich`, I get this error:

   ```
   ar: write error: No such file or directory
   *** Error code 1
   ```

   I've looked, and all the files are accessible and have the proper permissions.

   A: Check the amount of space in '`/tmp`'. This error is sometimes generated when there is insufficient space in '`/tmp`' to copy the archive (this is a step that `ar` takes when updating a library). The command `df /tmp` will show you how much space is available. Try to insure that at least twice the size of the library is available.

2. **Q:** When running make on `mpich`, I get errors when executing `ranlib`.

   A: Many systems implement `ranlib` with the `ar` command, and they use the '`/tmp`' directory by default because it "seems" obvious that using '`/tmp`' would be faster ('`/tmp`' is often a local disk). Unfortunately, a large number of systems have ridiculously small '`/tmp`' partitions, and making any use of '`/tmp`' is very risky. In some cases, the `ar` commands used by MPICH will succeed because they use the `l` option—this forces `ar` to use the local directory instead of '`/tmp`'. The `ranlib` command, on the other hand, may use '`/tmp`' and cannot be fixed.

   In some cases, you will find that the `ranlib` command is unnecessary. In these cases, you can reconfigure with `-noranlib`. If you must use `ranlib`, either reduce the space used in '`/tmp`' or increase the size of the '`/tmp`' partition (your system administrator will need to do this). There should be at least 20–30 MBytes free in '`/tmp`'.

3. **Q:** When doing the link test, the link fails and does not seem to find any of the MPI routines:

   ```
   /homes/them/burgess/mpich/lib/IRIX32/ch_p4/mpicc \
                                       -o overtake overtake.o test.o
   ld: WARNING 126: The archive \
      /homes/them/burgess/mpich/lib/IRIX32/ch_p4/libmpi.a \
                                   defines no global symbols. Ignoring.
   ```

```
  ld: WARNING 84: /usr/lib/libsun.a is not used for resolving any symbol.
ld: ERROR 33: Unresolved data symbol "MPI_COMM_WORLD" -- \
                                          1st referenced by overtake.o.
ld: ERROR 33: Unresolved text symbol "MPI_Send" -- \
                                          1st referenced by overtake.o.
...
```

A: Check that the `ar` and `ranlib` programs are compatible. One site installed the Gnu `ranlib` in such a way that it would be used with the vendors `ar` program, with which it was incompatible. Use the `-noranlib` option to `configure` if this is the case.

13.3.2 Workstation Networks

1. **Q:** When building mpich, the make fails with errors like this:

```
making p4 in directory lib
        make  libp4.a
        cc -Aa -g -I../include -I../../../../include   -c p4_globals.c
cc: "/usr/include/netinet/in.h", line 69: error 1000: Unexpected symbol: "u_long".
cc: "/usr/include/netinet/in.h", line 127: error 1000: Unexpected symbol: "u_short".
```

   etc.

   A: Check to see if `cc` is aliased (in C shell, do `alias cc`). If it is, either unalias it or set the environment variable `CC` to the full path for the compiler. To get the full path, do

```
unalias cc
setenv CC `which cc`
```

   and then reconfigure.

2. **Q:** When building the `ch_p4` device, I get errors of the form

```
making p4 in directory lib
        make  libp4.a
        cc -I../include -I../../../../include   -c p4_globals.c
        cc -I../include -I../../../../include   -c p4_MD.c
        cc -I../include -I../../../../include   -c p4_error.c
cc-142 cc: WARNING File = p4_error.c, Line = 152
  The number of old style and prototype parameters does not agree.
cc-142 cc: WARNING File = p4_error.c, Line = 162
  The number of old style and prototype parameters does not agree.
cc-142 cc: WARNING File = p4_error.c, Line = 169
  The number of old style and prototype parameters does not agree.
cc-142 cc: WARNING File = p4_error.c, Line = 174
  The number of old style and prototype parameters does not agree.
```

   A: These have to do with declarations for a signal handler, and can be ignored.

13.3.3 Cray T3D

1. **Q:** When linking I get

```
mppldr-133 cf77: CAUTION
    Unsatisfied external references have been encountered.

Unsatisfied external references
Entry name      Modules referencing entry

GETARG (equivalenced to $USX1)
                MPIR_GETARG
```

A: You may have specified the Fortran compiler with the `-fc` argument to configure. The MPICH Fortran implemenation of MPI uses a common Fortran extension, `GETARG`, to get the command line arguments. Most Fortran runtime systems support this, but Cray uses `call pxfgetarg(i,s,len(s),ierr)` instead. You can change the file '`src/env/farg.f`' manually to call the correct routine (but note that configure builds a new '`farg.f`' from '`farg.f.in`' each time that it is run).

On HP-UX version 10 systems, you can try configuring with `-fflags=+U77` and rebuilding MPICH.

13.3.4 Intel i860

1. **Q:** The link test fails on an Intel i860 with

```
        icc  -o overtake overtake.o test.o -L/mpich/lib/intelnx/  -lmpi  -lnode
/usr/ipsc/XDEV/i860/bin/ld860: Error: undefined symbol '_MPI_Keyval_create'
/usr/ipsc/XDEV/i860/bin/ld860: Fatal: no output file created
```

A: You are probably building MPICH on an old 386 running System V release 2. This version of Unix has very severe limitations on the length of filenames (more severe than we are willing to cater to). The specific problem here is that the name of the file '`mpich/src/context/keyval_create.c`' is too long for this system, and was not properly archived. You best bet is to build MPICH on a different, more modern system (for example, a Sun running SunOS or Solaris).

13.3.5 Intel Paragon

1. **Q:** I got the following messages when I tried to build on the Paragon:

```
PGC-W-0115-Duplicate standard type (init.c: 576)
PGC/Paragon Paragon Rel R5.0: compilation completed with warnings
PGC-W-0115-Duplicate standard type (init.c: 576)
PGC/Paragon Paragon Rel R5.0: compilation completed with warnings
```

A: This is because the compiler doesn't handle `long long int` but doesn't reject it either. It causes no harm.

2. **Q:** I get errors compiling or running Fortran programs. **A:**

   Fortran programs will need to use a *absolute* path for the '`mpif.h`' include file, due to a bug in the `if77` compiler (it searches include directories in the wrong order).

13.3.6 SGI

1. **Q:** The build on an SGI Power Challenge fails with

```
Signal: SIGSEGV in Back End Driver phase.
> ### Error:
> ### Signal SIGSEGV in phase Back End Driver -- processing aborted
> f77 ERROR:  /usr/lib64/cmplrs/be died due to signal 4
> f77 ERROR:  core dumped
> *** Error code 2 (bu21)
> *** Error code 1 (bu21)
> *** Error code 1 (bu21)
```

   A: Our information is that setting the environment variable `SGI_CC` to `-ansi` will fix this problem.

2. **Q:** The build on an SGI with architecture `IRIXN32` fails with

```
cc: Warning: -c should not be used with ucode -O3 -o32 \
             on a single file; use -j instead to get inter-module optimization.
```

   A: Amazingly, the standard `-c` option is *not valid* for the SGI compilers when both `-O3` and `-n32` are specified. This is a "feature" of the SGI compiler, and there is no way to work around this for MPICH (other than a massive and non-portable rewrite of all the '`Makefile`'s). Your only option is to not use the `-O3` option.

13.3.7 LINUX

1. **Q:** The link test failed on LINUX 3.0 with

```
...
cc  -o overtake overtake.o test.o -L/usr/local/mpich/lib/LINUX/ch_p4
-lmpi
overtake.o(.text+0x71): undefined reference to 'MPI_COMM_WORLD'
overtake.o(.text+0x82): undefined reference to 'MPIR_I_DOUBLE'
overtake.o(.text+0xe1): undefined reference to 'MPI_COMM_WORLD'
...
```

   A: We have been informed that there is a error in the `f77` script in some versions of LINUX which causes this problem. Try either getting a patch for the `f77` script or reconfiguring with `-nof77`.

13.3.8 IBM SP2

1. **Q:** Linking fails on an IBM SP2 for the `ch_mpl` device.

   A: You may have a version of the IBM MPL/POE software that already includes MPI. If that is the case, we recommend that you use that version. If you need to use MPICH, configure with `-mpilibname=mpich` and rebuild MPICH.

2. **Q:** When trying to link on an IBM SPx, I get the message from `mpirun`:

```
        mpCC  -o overtake overtake.o test.o -L/usr/local/src/Mpi/1.0.11/lib/rs6000/ch_eui   -lm
ld: 0711-317 ERROR: Undefined symbol: .mp_main
ld: 0711-317 ERROR: Undefined symbol: .mp_environ
ld: 0711-317 ERROR: Undefined symbol: .mpc_bsend
...
```

   A: Your IBM implementation does not seem to contain the MPL routines that MPICH uses to implement MPI. Your system may contain the IBM version of MPI; you should use that instead.

   We have been discussing with IBM a way to provide MPICH on SP systems that also have the IBM MPI; unfortunately, we have not been able to get the information that we need.

   In the interrim, you can do the following:

   Change the use of a library path ('`-L/usr/local/...`'), followed by '`-lmpi`', with an explicit file name. For example, instead of

```
-L/usr/local/src/Mpi/1.0.11/lib/rs6000/ch_eui -lmpi
```

   do

```
/usr/local/src/Mpi/1.0.11/lib/rs6000/ch_eui/libmpi.a
```

   This change needs to be made in the Makefiles and in the scripts such as '`mpicc`', '`mpif77`', and '`mpiCC`'.

13.3.9 DEC ULTRIX

1. **Q:** When trying to build, the `make` aborts early during the cleaning phase:

```
amon:MPICH/mpich>make clean
        /bin/rm -f *.o *~ nupshot
*** Error code 1
```

   A: This is a bug in the shell support on some DEC ULTRIX systems. You may be able to work around this with

```
setenv PROG_ENV SYSTEM_FIVE
```

   Configuring with `-make=s5make` may also work.

13.4 Problems in testing

The MPICH test suite, in '`examples/test`', performs a fairly complete test of an MPI implementation. If there is an error, it usually indicates a problem with the implementation of MPI; if you encounter such a problem, please report it to `mpi-bugs@mcs.anl.gov`. However, there are a few exceptions that are described here.

13.4.1 General

1. **Q:** The test '`pt2pt/structf`' fails with

   ```
   0 - Error in MPI_ADDRESS : Invalid argument: Address of location
   given to MPI_ADDRESS does not fit in Fortran integer
   [0] Aborting program!
   ```

   A: This is not an error; it is a gap in the MPI definition. This indicates that Fortran integers are not large enough to hold an address. This does indicate that MPI programs written in Fortran should not use the `MPI_Address` function on this system.

2. **Q:** The test '`env/timers`' fails with

   ```
   Timer around sleep(1) did not give 1 second; gave 0.399949
   ```

   A: The low-level software that MPICH uses probably makes use of the `SIGALRM` signal, thus denying it to the user's program. This is not an error (the standard permits systems to make use of any signals) though it is unfortunate.

   One system known to use `SIGALAM` is the IBM MPL/POE (device `ch_mpl`) software for using the High Performance Switch in the IBM SPx parallel computers.

Acknowledgments

The work described in this report has benefited from conversations with and use by a large number of people. We also thank those that have helped in the implementation of MPICH, particularly Patrick Bridges and Edward Karrels. Particular thanks goes to Nathan Doss and Anthony Skjellum for valuable help in the implementation and development of MPICH.

References

[1] Ralph Butler and Ewing Lusk. User's guide to the p4 parallel programming system. Technical Report ANL-92/17, Argonne National Laboratory, October 1992.

[2] Ralph Butler and Ewing Lusk. Monitors, messages, and clusters: The p4 parallel programming system. *Parallel Computing*, 20:547–564, April 1994. (Also Argonne National Laboratory Mathematics and Computer Science Division preprint P362-0493).

[3] William Gropp and Ewing Lusk. An abstract device definition to support the implementation of a high-level message-passing interface. Technical Report MCS-P342-1193, Argonne National Laboratory, 1993.

[4] William Gropp and Ewing Lusk. Scalable Unix tools on parallel processors. In *Proceedings of the Scalable High Performance Computing Conference*, pages 56–62. IEEE, 1994.

[5] William Gropp and Ewing Lusk. User's guide for `mpich`, a portable implementation of MPI. Technical Report ANL-96/6, Argonne National Laboratory, 1996.

[6] William Gropp and Ewing Lusk. A high-performance MPI implementation on a shared-memory vector supercomputer. *Parallel Computing*, 22(11):1513–1526, January 1997.

[7] William Gropp, Ewing Lusk, Nathan Doss, and Anthony Skjellum. A high-performance, portable implementation of the MPI message-passing interface standard. *Parallel Computing*, 22:789–828, 1996.

[8] Virginia Herrarte and Ewing Lusk. Studying parallel program behavior with `upshot`. Technical Report ANL–91/15, Argonne National Laboratory, Argonne, IL 60439, 1991.

[9] Edward Karrels and Ewing Lusk. Performance analysis of MPI programs. In Jack Dongarra and Bernard Tourancheau, editors, *Proceedings of the Workshop on Environments and Tools For Parallel Scientific Computing*. SIAM Publications, 1994.