Message Passing Interface Quick Reference in C

```
#include <mpi.h>
```

Blocking Point-to-Point

Send a message to one process. (§3.2.1)
```
int MPI_Send (void *buf, int count,
    MPI_Datatype datatype, int dest, int
    tag, MPI_Comm comm)
```

Receive a message from one process. (§3.2.4)
```
int MPI_Recv (void *buf, int count,
    MPI_Datatype datatype, int source, int
    tag, MPI_Comm comm, MPI_Status *status)
```

Count received data elements. (§3.2.5)
```
int MPI_Get_count (MPI_Status *status,
    MPI_Datatype datatype, int *count)
```

Wait for message arrival. (§3.8)
```
int MPI_Probe (int source, int tag,
    MPI_Comm comm, MPI_Status *status)
```

Related Functions: MPI_Bsend, MPI_Ssend, MPI_Rsend, MPI_Buffer_attach, MPI_Buffer_detach, MPI_Sendrecv, MPI_Sendrecv_replace, MPI_Get_elements

Non-blocking Point-to-Point

Begin to receive a message. (§3.7.2)
```
int MPI_Irecv (void *buf, int count,
    MPI_Datatype, int source, int tag,
    MPI_Comm comm, MPI_Request *request)
```

Complete a non-blocking operation. (§3.7.3)
```
int MPI_Wait (MPI_Request *request,
    MPI_Status *status)
```

Check or complete a non-blocking operation. (§3.7.3)
```
int MPI_Test (MPI_Request *request, int
    *flag, MPI_Status *status)
```

Check message arrival. (§3.8)
```
int MPI_Iprobe (int source, int tag,
    MPI_Comm comm, int *flag, MPI_Status
    *status)
```

Related Functions: MPI_Isend, MPI_Ibsend, MPI_Issend, MPI_Irsend, MPI_Request_free, MPI_Waitany, MPI_Testany, MPI_Waitall, MPI_Testall, MPI_Waitsome, MPI_Testsome, MPI_Cancel, MPI_Test_cancelled

Persistent Requests

Related Functions: MPI_Send_init, MPI_Bsend_init, MPI_Ssend_init, MPI_Rsend_init, MPI_Recv_init, MPI_Start, MPI_Startall

Derived Datatypes

Create a strided homogeneous vector. (§3.12.1)
```
int MPI_Type_vector (int count, int
    blocklength, int stride, MPI_Datatype
    oldtype, MPI_Datatype *newtype)
```

Save a derived datatype (§3.12.4)
```
int MPI_Type_commit (MPI_Datatype
    *datatype)
```

Pack data into a message buffer. (§3.13)
```
int MPI_Pack (void *inbuf, int incount,
    MPI_Datatype datatype, void *outbuf,
    int outsize, int *position, MPI_Comm
    comm)
```

Unpack data from a message buffer. (§3.13)
```
int MPI_Unpack (void *inbuf, int insize,
    int *position, void *outbuf, int
    outcount, MPI_Datatype datatype,
    MPI_Comm comm)
```

Determine buffer size for packed data. (§3.13)
```
int MPI_Pack_size (int incount,
    MPI_Datatype datatype, MPI_Comm comm,
    int *size)
```

Related Functions: MPI_Type_contiguous, MPI_Type_hvector, MPI_Type_indexed, MPI_Type_hindexed, MPI_Type_struct, MPI_Address, MPI_Type_extent, MPI_Type_size, MPI_Type_count, MPI_Type_lb, MPI_Type_ub, MPI_Type_free

Collective

Send one message to all group members. (§4.4)
```
int MPI_Bcast (void *buf, int count,
    MPI_Datatype datatype, int root,
    MPI_Comm comm)
```

Receive from all group members. (§4.5)
```
int MPI_Gather (void *sendbuf, int
    sendcount, MPI_Datatype sendtype, void
    *recvbuf, int recvcount, MPI_Datatype
    recvtype, int root, MPI_Comm comm)
```

Send separate messages to all group members. (§4.6)
```
int MPI_Scatter (void *sendbuf, int
    sendcount, MPI_Datatype sendtype, void
    *recvbuf, int recvcount, MPI_Datatype
    recvtype, int root, MPI_Comm comm)
```

Combine messages from all group members. (§4.9.1)
```
int MPI_Reduce (void *sendbuf, void
    *recvbuf, int count, MPI_Datatype
    datatype, MPI_Op op, int root, MPI_Comm
    comm)
```

Related Functions: MPI_Barrier, MPI_Gatherv, MPI_Scatterv, MPI_Allgather, MPI_Allgatherv, MPI_Alltoall, MPI_Alltoallv, MPI_Op_create, MPI_Op_free, MPI_Allreduce, MPI_Reduce_scatter, MPI_Scan

Groups

Related Functions: MPI_Group_size, MPI_Group_rank, MPI_Group_translate_ranks, MPI_Group_compare, MPI_Comm_group, MPI_Group_union, MPI_Group_intersection, MPI_Group_difference, MPI_Group_incl, MPI_Group_excl, MPI_Group_range_incl, MPI_Group_range_excl, MPI_Group_free

Basic Communicators

Count group members in communicator. (§5.4.1)
```
int MPI_Comm_size (MPI_Comm comm, int
    *size)
```

Determine group rank of self. (§5.4.1)
```
int MPI_Comm_rank (MPI_Comm comm, int
    *rank)
```

Duplicate with new context. (§5.4.2)
```
int MPI_Comm_dup (MPI_Comm comm, MPI_Comm
    *newcomm)
```

Split into categorized sub-groups. (§5.4.2)
```
int MPI_Comm_split (MPI_Comm comm, int
    color, int key, MPI_Comm *newcomm)
```

Related Functions: MPI_Comm_compare, MPI_Comm_create, MPI_Comm_free,

MPI_Comm_test_inter, MPI_Comm_remote_size, MPI_Comm_remote_group, MPI_Intercomm_create, MPI_Intercomm_merge

Communicators with Topology

Create with cartesian topology. (§6.5.1)
```
int MPI_Cart_create (MPI_Comm comm_old,
    int ndims, int *dims, int *periods, int
    reorder, MPI_Comm *comm_cart)
```

Suggest balanced dimension ranges. (§6.5.2)
```
int MPI_Dims_create (int nnodes, int
    ndims, int *dims)
```

Determine rank from cartesian coordinates. (§6.5.4)
```
int MPI_Cart_rank (MPI_Comm comm, int
    *coords, int *rank)
```

Determine cartesian coordinates from rank. (§6.5.4)
```
int MPI_Cart_coords (MPI_Comm comm, int
    rank, int maxdims, int *coords)
```

Determine ranks for cartesian shift. (§6.5.5)
```
int MPI_Cart_shift (MPI_Comm comm, int
    direction, int disp, int *rank_source,
    int *rank_dest)
```

Split into lower dimensional sub-grids. (§6.5.6)
```
int MPI_Cart_sub (MPI_Comm comm, int
    *remain_dims, MPI_Comm *newcomm)
```

Related Functions: MPI_Graph_create, MPI_Topo_test, MPI_Graphdims_get, MPI_Graph_get, MPI_Cartdim_get, MPI_Cart_get, MPI_Graph_neighbors_count, MPI_Graph_neighbors, MPI_Cart_map, MPI_Graph_map

Communicator Caches

Related Functions: MPI_Keyval_create, MPI_Keyval_free, MPI_Attr_put, MPI_Attr_get, MPI_Attr_delete

---

LAM & MPI Information

1224 Kinnear Rd.
Columbus, Ohio 43212
614-292-8492

lam@tbag.osc.edu

http://www.osc.edu/lam.html
ftp://tbag.osc.edu/pub/lam

Error Handling

Related Functions: MPI_Errhandler_create, MPI_Errhandler_set, MPI_Errhandler_get, MPI_Errhandler_free, MPI_Error_string, MPI_Error_class

Environmental

Determine wall clock time. (§7.4)
```
double MPI_Wtime (void)
```

Initialize MPI. (§7.5)
```
int MPI_Init (int *argc, char ***argv)
```

Cleanup MPI. (§7.5)
```
int MPI_Finalize (void)
```

Related Functions: MPI_Get_processor_name, MPI__Wtick, MPI_Initialized, MPI_Abort, MPI_Pcontrol

Constants

Wildcards (§3.2.4)
```
MPI_ANY_TAG, MPI_ANY_SOURCE
```

Elementary Datatypes (§3.2.2)
```
MPI_CHAR, MPI_SHORT, MPI_INT, MPI_LONG,
MPI_UNSIGNED_CHAR, MPI_UNSIGNED_SHORT,
MPI_UNSIGNED, MPI_UNSIGNED_LONG,
MPI_FLOAT, MPI_DOUBLE, MPI_LONG_DOUBLE,
MPI_BYTE, MPI_PACKED
```

Reserved Communicators (§5.2.4)
```
MPI_COMM_WORLD, MPI_COMM_SELF
```

Reduction Operations (§4.9.2)
```
MPI_MAX, MPI_MIN, MPI_SUM, MPI_PROD,
    MPI_BAND, MPI_BOR, MPI_BXOR, MPI_LAND,
    MPI_LOR, MPI_LXOR
```

Running MPI With LAM 5.2 Quick Reference

Session Management

Confirm a group of hosts.
```
recon -v <hostfile>
```

Start LAM on a group of hosts.
```
lamboot -v <hostfile>
```

Terminate LAM.
```
wipe -v <hostfile>
```

Hostfile Syntax
```
# comment
<hostname> <userid>
<hostname> <userid>
...etc...
```

Compilation

Compile a program for LAM.
```
hcc -o <binary> <source> -I<incdir>
    -L<libdir> -l<lib>
```

Processes and Messages

Start an SPMD application.
```
mpirun -v -s <src_node> -c <copies>
    <nodes> <program> -- <args>
```

Start a MIMD application.
```
mpirun -v <appfile>
```

Appfile Syntax
```
# comment
<program> -s <src_node> <nodes> -- <args>
<program> -s <src_node> <nodes> -- <args>
...etc...
```

Examine the state of processes.
```
mpitask
```

Examine the state of messages.
```
mpimsg
```

Cleanup all processes and messages.
```
lamclean -v
```

Resources

Monitor remote and parallel files.
```
fstate <nodes>
```

Control message buffer parameters.
```
bfctl <nodes>
```